ONSITE WASTEWATER DISPOSAL FEASIBILTY STUDY

FOR THE

RELIC WINE CELLARS USE PERMIT

LOCATED AT:
2400 Soda Canyon Road
Napa, CA 94558
NAPA COUNTY APN 032-090-024

PREPARED FOR:
Relic Wine Cellars
c/o Schatzi Throckmorton & Michael Hirby
Post Office Box 327
St. Helena, CA 94574
Telephone: (707) 967-9380

PREPARED BY:



2074 West Lincoln Avenue Napa, California 94558 Telephone: (707) 320-4968 www.appliedcivil.com

Job Number: 09-124



Michael R. Mulsath

Michael R. Muelrath R.C.E. 67435

3/31/2010

Date

TABLE OF CONTENTS

LIST OF APPENDICES	iii
INTRODUCTION	1
SOILS INFORMATION	2
PREDICTED WASTEWATER FLOW	2
Winery Process Wastewater	2
Winery Sanitary Wastewater	3
Employees	3
Daily Tours and Tastings	3
Private Food and Wine Events — Meal Prepared Offsite	3
Private Food and Wine Events – Meal Prepared Onsite	3
Total Peak Winery Sanitary Wastewater Flow	3
Combined Peak Wastewater Flow	4
recommendations	4
Option #1 - Combined Sanitary and Process Wastewater Disposal Field	4
Required Disposal Field Area	4
Available Disposal Field Area	5
200% Reserve Area	5
Septic Tank Capacity	5
Option #2 – Sanitary Wastewater Subsurface Drip Disposal and Process Wastewater	
Required Disposal Field Area	6
Available Disposal Field Area	6
200% Reserve Area	6
Septic Tank Capacity	6
Winery Process Wastewater Disposal	6
CONCLUSION	6

LIST OF APPENDICES

APPENDIX I:	Site Topography Map	7
APPENDIX 2:	Relic Wine Cellars Use Permit Site Plan	9
APPENDIX 3:	Site Evaluation Reports and Test Pit MapsI	I

INTRODUCTION

Relic Wine Cellars is applying for a Use Permit to construct and operate a new winery at their property located at 2400 Soda Canyon Road, in Napa County, California. The subject property is located along the east side of Soda Canyon Road, approximately five miles northeast of the intersection of Soda Canyon Road and Silverado Trail. The subject parcel is also known as Napa County Assessor's Parcel Number 032-090-024.

There is an existing well and driveway on the subject parcel but no existing structures. The use permit application under consideration proposes the construction of a new winery building and winery cave. The details of the proposed winery are as follows:

- Wine Production:
 - o 20,000 gallons of wine per year
 - Full wine production including:
 - Crushing
 - Fermenting
 - Aging
 - Bottling
- Employees:
 - o Four (4) full-time employees
- Marketing Plan:
 - Daily Tours and Tastings by Appointment
 - 20 visitors per day maximum
 - Private Food and Wine Tasting for Trade
 - 6 per year
 - 25 guests maximum
 - o Private Food and Wine Events
 - 6 per year
 - 25 guests maximum
 - Wine Auction & Release Party Events
 - 2 per year
 - 50 guests maximum
 - Portable sanitary facilities

Relic Wine Cellars has requested that Applied Civil Engineering Incorporated (ACE) evaluate the feasibility of disposing of the winery process wastewater and domestic sanitary wastewater that will be generated by the proposed winery via an onsite wastewater disposal system.

The remainder of this report describes the onsite soil conditions, the predicted process and sanitary wastewater flows and outlines the conceptual design of an onsite wastewater disposal system to serve the proposed winery.



SOILS INFORMATION

The United States Department of Agriculture Soil Conservation Service Soils Map for Napa County shows a majority of the parcel mapped as Aiken loam, 30 to 50 percent slopes. The steeply sloping eastern corner of the property is mapped as Rock outcrop and the western panhandle near Soda Canyon Road is mapped as Aiken loam, 15 to 30 percent slopes.

Two recent site specific soils evaluations have been conducted. The first site evaluation was conducted by Always Engineering on May 15, 2007 in an effort to locate an area to install a septic system for a new residence that was never constructed. The most current site evaluation was performed by Applied Civil Engineering Incorporated on November 12, 2009. The purpose of that site evaluation was to determine if additional suitable area could be located to accommodate the wastewater flows from a winery.

In total, 21 test pits were excavated, observed and recorded during the two site evaluations. The site evaluation reports indicate variable acceptable soil depths ranging from 12 inches to 50 inches of acceptable clay loam / sandy clay loam soil overlying dense sandy clay and / or bedrock. Analysis of soil texture was based on field methods and laboratory testing was not performed. Perched groundwater was not noted in any of the test pits at the time of excavation. Please refer to the Site Evaluation Reports in Appendix 3 for further soil information.

PREDICTED WASTEWATER FLOW

Winery Process Wastewater

We have used the generally accepted standard that six gallons of winery process wastewater are generated for each gallon of wine that is produced each year and that 1.5 gallons of wastewater are generated during the crush period for each gallon of wine that is produced. Based on the size of the winery and the expectation that both white and red wine will be produced at the winery, we have assumed a 45 day crush period. Using these assumptions, the annual, average daily and peak winery process wastewater flows are calculated as follows:

Annual Winery Process Wastewater Flow =
$$\frac{20,000 \text{ gallons wine}}{\text{year}} \times \frac{6 \text{ gallons wastewater}}{1 \text{ gallon wine}}$$

Annual Winery Process Wastewater Flow = 120,000 gallons per year

Average Daily Process Wastewater Flow =
$$\frac{120,000 \text{ gallons wastewater}}{\text{year}} \times \frac{1 \text{ year}}{365 \text{ days}}$$

Average Daily Winery Process Wastewater Flow = 329 gallons per day

Peak Winery Process Wastewater Flow =
$$\frac{20,000 \text{ gallons wine}}{\text{year}} \times \frac{\text{I.5 gallons wastewater}}{\text{I gallon wine}} \times \frac{\text{I year}}{\text{45 crush days}}$$

Peak Winery Process Wastewater Flow = 667 gallons per day (gpd)

Winery Sanitary Wastewater

The peak sanitary wastewater flow from the winery is calculated based on the number of winery employees, the number of daily visitors for tours and tastings and the number of guests attending marketing events. In accordance with Table 4 of the Napa County Environmental Management Department "Regulations for Design, Construction, and Installation of Alternative Sewage Treatment Systems" we have used a design flow rate of 15 gallons per day per employee and 3 gallons per day per visitor for tours and tastings. Table 4 does not specifically address design wastewater flows for guests at marketing events. We have estimated 5 gallons of wastewater per guest at marketing events since meals will be prepared offsite. Based on these assumptions, the peak winery sanitary wastewater flows are calculated as follows:

Employees

Peak Sanitary Wastewater Flow = 4 employees X 15 gpd per employee

Peak Sanitary Wastewater Flow = 60 gpd

Daily Tours and Tastings

Peak Sanitary Wastewater Flow = 20 visitors per day X 3 gallons per visitor

Peak Sanitary Wastewater Flow = 60 gpd

Private Food and Wine Events - Meal Prepared Offsite

Peak Sanitary Wastewater Flow = 25 guests X 5 gallons per guest

Peak Sanitary Wastewater Flow = 125 gpd

Total Peak Winery Sanitary Wastewater Flow

Assuming that daily tours and tastings and private food and wine events may occur on the same day and that all events with more than 25 guests will utilize portable sanitary facilities, the total peak winery sanitary wastewater flow is calculated as follows:

Total Peak Winery Sanitary Wastewater Flow = 60 gpd + 60 gpd + 125

Total Peak Winery Sanitary Wastewater Flow = 245 gpd



JUL 1 3 2010

NAPA CO. CONSERVATION DEVELOPMENT & PLANNING DEPT.

Combined Peak Wastewater Flow

Combined Peak Wastewater Flow = Peak Winery Process Wastewater Flow + Total Peak Winery Sanitary Wastewater Flow

Combined Peak Flow = 667 gpd + 245 gpd

Combined Peak Flow = 912 gpd, use 1,000 gpd

RECOMMENDATIONS

Given the soil conditions reported from the site evaluations, the proposed site plan layout and the design wastewater flows calculated above, we recommend that the area in the vicinity of the Always Engineering Test Pits #2 and #3 be used for wastewater disposal. We have identified two possible scenarios for disposing of the process and sanitary wastewater generated at the subject parcel:

Option #I - Combined Sanitary and Process Wastewater Disposal Field

Option #2 - Sanitary Wastewater Disposal Field and Process Wastewater Hold and Haul

The decision about which type of wastewater disposal system to implement will be made by the property owner and the engineer at the time of building permit submittal.

The following sections of this report outline the conceptual design of the wastewater disposal systems for both of these options.

Option #1 - Combined Sanitary and Process Wastewater Disposal Field

In this scenario all sanitary and process wastewater would be treated and disposed of onsite in a subsurface drip type septic system.

Required Disposal Field Area

The soil encountered in the proposed disposal field area consists of sandy clay loam with a strong subangular blocky structure. We recommend a soil application rate of 0.6 gallons per square foot per day. Since the slope of the existing ground in the disposal field area is in excess of 20% we recommend that the drip tubing spacing be increased from the standard two foot spacing to three feet. This will increase the required disposal field area by 50%. The required disposal field area is calculated as follows:

Required Disposal Field Area =
$$\frac{1,000 \text{ gpd}}{0.6 \text{ gpd per square foot}} \times 150\%$$

Required Disposal Field Area = 2,500 square feet



JUL 1 3 2010

NAPA CO. CONSERVATION DEVELOPMENT & PLANNING DEPT.

Available Disposal Field Area

Based on the topographic mapping prepared by REB Engineering, ACE has determined that there is enough area to install the required 2,500 square feet of subsurface drip disposal field in the vicinity of Always Engineering Test Pits #2 and #3. The conceptual layout of the disposal field is shown on the Relic Wine Cellars Use Permit Site Plan, prepared by Albion Surveys, which is included in reduced format in Appendix 2 of this document.

200% Reserve Area

Napa County code requires that an area be set aside to accommodate a future onsite wastewater disposal system in the event that the primary system fails. For subsurface drip disposal fields, the reserve area must be two times the area of the primary system. Based on the topographic map prepared by REB Engineering, ACE has determined that there is enough area to set aside for an additional 5,000 square feet of subsurface drip disposal field in the vicinity of Test Pits #1, #2, #3 and #5.

Septic Tank Capacity

The process and sanitary wastewater from the winery buildings should be collected in septic tanks and must be treated to Napa County Environmental Management Department Pretreated Effluent requirements ($BOD_5 < 30 \text{ mg/l}$ and TSS < 30 mg/l) prior to delivery to the disposal field.

We recommend that at least two 1,500 gallon septic tanks be installed to provide a minimum of three to five days of hydraulic retention time for peak winery process wastewater flows. Furthermore, for ease of operation and maintenance, we recommend that the sanitary wastewater flows from the winery building be kept separate from the process wastewater flows and be directed to a separate 1,200 gallon septic tank. Effluent from the winery process wastewater septic tanks and effluent from the winery sanitary wastewater septic tank should join in a common vessel from which it will be dosed to the treatment system. Depending on the type of treatment system selected, additional septic tanks may be required. Furthermore, a sump tank and pumping system will be required to deliver effluent from the treatment system to the disposal field.

Option #2 - Sanitary Wastewater Subsurface Drip Disposal and Process Wastewater Hold and Haul

In this scenario the sanitary wastewater would be disposed of in a subsurface drip disposal field and process wastewater would be temporarily stored and then would be hauled offsite for treatment and disposal by the Napa Sanitation District, East Bay Municipal Utility District or a similar municipal wastewater treatment plant.



JUL 1 8 2010

NAPA CO. CONSERVATION DEVELOPMENT & PLANNING DEPT.

Required Disposal Field Area

Sanitary wastewater disposal is the same as that described in Option #1 above. The required disposal field area is calculated as follows:

Required Disposal Field Area =
$$\frac{245 \text{ gpd}}{0.6 \text{ gpd per square foot}} \times 150\%$$

Required Disposal Field Area = 613 square feet

Available Disposal Field Area

The disposal field would be located in the same area as described in Option #1 above.

200% Reserve Area

The 200% reserve area would be located in the same area as described in Option #1 above.

Septic Tank Capacity

Sanitary wastewater septic tank capacity and pretreatment requirements are similar to Option #I described above.

Winery Process Wastewater Disposal

The winery process wastewater hold and haul system must be designed to hold at least seven days of peak flow. The required holding tank volume is calculated as follows:

Required Holding Tank Volume = 667 gallons per day × 7 days

Required Holding Tank Volume = 4,669 gallons

The holding tank must have a water level alarm and be designed and constructed in accordance with the requirements outlined in the Napa County Environmental Management Department Hold and Haul for Winery Process Wastewater Management information sheet. Based on the anticipated wastewater flows and site access conditions it is likely that a 3,500 gallon septic pumping truck would service the hold and haul system. This would mean that pumping of the hold and haul system would need to occur one to two times per week during crush and approximately two to three times per month outside of the crush season.

CONCLUSION

It is our opinion that the wastewater from the proposed winery can be accommodated in either of the two options previously described. Full design calculations and construction plans for the wastewater system(s) should be prepared in accordance with Napa County Environmental Management Department standards at the time of building permit application.

6

RECEIVED

APPENDIX I: Site Topography Map

SITE TOPOGRAPHY MAP

REPRESENTS A PORTION OF THE USGS 7.5 MINUTE QUADRANGLE "YOUNTVILLE" REPRODUCED FROM NATIONAL GEOGRAPHIC TOPO! OUTDOOR RECREATION MAPPING SOFTWARE




.22°19.000' W

122°18,000' W

122°17.000' W

WG584






2074 West Lincoln Avenue Napa, CA 94558 (707)320-4968 (707)320-2395 Fax **RELIC WINE CELLARS**

2400 SODA CANYON ROAD NAPA, CA 94558 APN 032-090-024

100 110 00 101

APPENDIX 2: Relic Wine Cellars Use Permit Site Plan



APPENDIX 3: Site Evaluation Reports and Test Pit Maps

SITE EVALUATION REPORT

Page_1_of_5

Please attach an 8.5" x 11" plot map showing the locations of all test pits triangulated from permanent landmarks or known property corners. The map must be drawn to scale and include a North arrow, surrounding geographic and topographic features, direction and % slope, distance to drainages, water bodies, potential areas for flooding, unstable landforms, existing or proposed roads, structures, utilities, domestic water supplies, wells, ponds, existing wastewater treatment systems and facilities.

Permit #: E07-00	0 Z68
APN: 03Z - 090	750-c
(County Use Only) Reviewed by:	Date: 6.4.07

PLEASE PRINT OR TYPE ALL INFORMATION

Property Owner	<u> </u>			
Wict	New Construction	Addition	☐ Remodel ☐ Relocati	ion
Property Owner Mailing Address	☐ Other:			
ά	Residential - # o	Bedrooms: 5	Design Flow: (Q)) gpd
State Zip Site Address/Location 2400 Soba CANYON RD. NAPA, CA	☐ Commercial – Ty Sanitary Waste: ☐ Other:	gpd	Process Waste:	gpd
	Sanitary Waste:	gpd	Process Waste:	gpd
Evaluation Conducted By: Company Name Always Engineering Ben W. Mon Mailing Address: 6865 LOIS LANE City State Zip FORESTVILLE CA 95	100 136	Telephone Numb	318-7099	ntist)
Groundwater Monte day in the	Hydrometer test perfor Bulk Density test perfo Groundwater Monitorin	gal. /sq. ft. /day): nmended: ance to nearest w med? No med? No	PRIMARY)
- SEE ATTACHED REPORT		- 14		The state of the s
				- 1

Always Engineering, Inc. 14479 Western Avenue Guerneville, CA 95446 phone (707) 318-7099 Soil Profile Data

Chedied By Davit Chare
Date: 5/15/2007

Jack and Jane McSorley

2400 Soda Caryon Road, Napa, Ca


APN: 032-090-024


Londay B

Byan 915/2017

	E HORIZON BOUNDARY					CONSISTENCY		POROSITY	ROOTS	MOTTLING	Notes	
PROFILE	DEPTH	BOUNDARY	% ROCK	TEXTURE	STRUCTURE	Side Well	Ped	Wet	POROSITT	KODIO	and the same	
TP1	8lop	e = 30%	Hillside Area				<u> </u>				1	
A	22	О	10	SCL	SSAB	VF	VH	SS	C,C	M.C	0	
В	48	С	10	SCL	SSAB	VF	VH	SS	C,C	F,F	0	
C	54	-	20	8C	SAB	VF	VH	SS	F,F	0	0	
TP2	Ston	e ≃ 30%	Hillside Area			т			7		7	
	22	C	10	SCL	SSAB	VF	VH	88	c.c	M.C	0	
B	32	D _o	10	SCL	SSAB	VF VF	VH	88	C,C	C'W	0	
-	50	D	10	SCL	SSAB	VF	VH	\$S	C,M	F,M	0	
Ď	80		20	SC	SAB	VF VF	\int	ss	FF		0	
<u> </u>	00		20	30	GAB 1	<u></u>	VII.		1 15		<u> </u>	
ТРЗ 💮	Slope =	20% - 30%	Araa .Araa									
A	30	D	30	SCL	SSAB	VF	VH	88	c,c	M,VC	0	
8	34	-	65	SCL/ROCK	88	ExF	ExF	SS	M.C	C,M	0	
С		, rock begins at									•	
TP4		20% - 30%									<u> </u>	
							VH	ss	c,c	M,VC		
TP4	Slope=	20% - 30%	Hillelde Area								<u> </u>	
TP4	Slope=	20% - 30% C	Hillelde Area	SCL	S5AB	VF	VH	ss	c,c	M,VC		
TP4 A B C	Slope = 18 33	20% - 30% C	Hillelde Area 30 76	SCL	S5AB	VF	VH	ss	c,c	M,VC		
TP4 A B C	Slope = 18 33 Slope	20% - 30% C	Hillelde Area	SCL	S5AB	VF	VH	ss	c,c	M,VC		
TP4 A B C	Slope = 18 33	20% - 30% C	Hillside Area 30 76 Hillside Area	SCL SCL/ROCK	S5AB SB	VF ExF	VH ExF	\$8 \$\$	C,C N,C	M,VC C,M	0 0	
TP4 A B C TP5 A	Slope = 18 33 Slope	20% - 30% C -	Hilfelde Area 30 76 Hilfelde Area 15	SCL SCL/ROCK	SSAB SB	VF ExF	VH ExF	SS SS	C,C N,C	M,VC C,M	0 0	
TP4 A B C TP5 A B C	Slope = 18 33	20% - 30% C	Hiltelde Area 30 75 Hiltelde Area 15 40 75	SCL SCL/ROCK SCL SCL	SSAB SB SSAB SSAB	VF ExF	VH ExF	\$8 \$\$ \$\$ \$\$	C,C M,C M,C	M,VC C,M	0 0	
TP4 A B C TP5 A B C	Slope = 18 33	20% - 30% C	Hiltelde Area 30 76 Hiltelde Area 15 40 75	SCL SCL/ROCK SCL SCL SCL SCL/ROCK	SSAB SB SSAB SSAB SSAB SB	VF ExF VF VF ExF	VH EXF	\$8 \$8 \$8 \$8 \$8 \$8 \$8	C,C M,C M,C C,M	M,VC C,M M,VC C,C	0 0 0 0 0	
TP4 A B C TP5 A B C TP6 A	Slope = 18 33	20% - 30% C	Hiltelde Area 30 76 Hiltelde Area 40 75 Hiltelde Area 10	SCL SCL/ROCK SCL SCL SCL SCL SCL SCL/ROCK	SSAB SSAB SSAB SB	VF ExF VF VF ExF	VH ExF	\$8 \$8 \$8 \$8 \$8 \$8 \$8	C,C M,C M,C C,M F,F	M,VC C,M M,VC C,C 0	0 0 0 0 0	
TP4 A B C TP5 A B C TP6 A B C TP6 A B B	Slope = 18 33	20% - 30% C	Hiltelde Area 30 76 Hiltelde Area 15 40 75	SCL SCL/ROCK SCL SCL SCL SCL/ROCK	SSAB SB SSAB SSAB SSAB SB	VF ExF VF VF ExF	VH EXF	\$8 \$8 \$8 \$8 \$8 \$8 \$8	C,C M,C M,C C,M	M,VC C,M M,VC C,C	0 0 0 0 0	
TP4 A B C TP5 A B C TP6 A	Slope = 18 33	20% - 30% C	Hiltelde Area 30 76 Hiltelde Area 40 75 Hiltelde Area 10	SCL SCL/ROCK SCL SCL SCL SCL SCL SCL/ROCK	SSAB SSAB SSAB SB	VF ExF VF VF ExF	VH ExF	\$8 \$8 \$8 \$8 \$8 \$8 \$8	C,C M,C M,C C,M F,F	M,VC C,M M,VC C,C 0	0 0 0 0 0	
TP4 A B C TP5 A B C TP6 A B C TP6 A B B	Slope = 18 33	20% - 30% C 30% D D	Hiltelde Area 30 75 Hiltelde Area 15 40 75 Hiltelde Area 10 40	SCL SCL/ROCK SCL SCL SCL SCL SCL SCL/ROCK	SSAB SSAB SSAB SB SSAB SSAB SSAB SSAB S	VF ExF VF VF ExF	VH ExF	\$8 \$8 \$8 \$8 \$8 \$8 \$8	C,C M,C M,C C,M F,F	M,VC C,M M,VC C,C 0	0 0 0 0 0	
TP4 A B C TP5 A B C TP6 A B C	Slope = 18 33	20% - 30% C 30% D D	Hiltelde Area 30 75 Hiltelde Area 15 40 75 Hiltelde Area 10 40	SCL SCL/ROCK SCL SCL SCL SCL SCL/ROCK SCL SCL/ROCK	SSAB SSAB SSAB SB SSAB SSAB SSAB SSAB S	VF ExF VF VF ExF	VH ExF	\$8 \$8 \$8 \$8 \$8 \$8 \$8	C,C M,C M,C C,M F,F	M,VC C,M M,VC C,C 0	0 0 0 0 0	
TP4 A B C TP5 A B C TP6 A B C TP7	Slope = 18 33	20% - 30% C - 30% D D - 30% C D 5% - 10%	Hiltelde Area 30 75 Hiltelde Area 15 40 75 Hiltelde Area 10 40 Between Sada C	SCL SCL/ROCK SCL SCL SCL SCL SCL/ROCK SCL SCL/ROCK	SSAB SSAB SSAB SSAB SSAB SSAB SSAB SSAB	VF ExF VF ExF VF ExF	VH EXF H H VH VH EXH	\$8 \$8 \$8 \$8 \$8 \$8 \$8 \$8	C,C M,C M,C C,M F,F	M,VC C,M N,VC C,C 0	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	

USOA Texture Class	Structure		Consistence		Porosity	Roots	Molling
C = Gineral S-Saird LS = Learny Sand SCL = Sandy Clay Learn SCL = Sith Sith Learn SCL = Sith Clay Learn SC = Sith Clay Learn SC = Sandy Clay SC = Sith Clay C = Sith Clay C = Sith Clay	G = Granular PL = Platey PR = Printrate C.pr = Columns BK = Blocky ABIC = Argubar Blocky BK = Subangular Blocky M= Messave Grade: Week = 1 Med = 2 Strong = 3 Size: Fire = F Modkm = N Gourse = C Vary Costse = VC	Edie Wali t= Loase t= Loase t= Segithy Hard H= Hard Vri = Very Hard Earl = Edromoly Hard	FRB = Friable F = Fitm VF = Very Frim	Wet NS = NonShicky S = Slightly Slicky S = Sticky VS = Very Slicky NP = NonPlastic SP = Slightly Plastic P = Ptale VP = Very Plastic	Qty: 1 = Few 2 = Centrol 3 ™ Mary Stor: VF = Vecy Five F = Five 44 ™ Medium C = Coerse VG = Very Coerse	Cty: 1 = Few 2 = Cormon 3 = Merry Size: F = Fine N = Medium C = Course VC = Very Coerre ExC = Externey Course Dec/SS = Oecomposing Sendstone SMPL = Sample	Child / Nedoct** O/R Chy: 1 = Fevr 2 = Common 3= Many Size; F = Fine M = Medium C = Coarse Confract F = Faid D = Diploct P = Prominant





Napa County Department of **Environmental Management**

SITE EVALUATION REPORT

Page	<u>1_</u> o	f <u>4</u>
------	-------------	------------

Please attach an 8.5" x 11" plot map showing the locations of all test pits triangulated from permanent landmarks or known property corners. The map must be drawn to scale and include a North arrow, surrounding geographic and topographic features, direction and % slope, distance to drainages, water bodies, potential areas for flooding, unstable landforms, existing or proposed roads, structures, utilities, domestic water supplies, wells, ponds, existing wastewater treatment systems and facilities.

Permit #:E09-00500		
APN: 032-090-024		
(County Use Only) Reviewed by:	Date:	

PLEASE PRINT OR TYPE ALL INFORMATION

Property Owner Michael Hirby Schatzi Throckmorton			Х	±	□ Remodel □ Relocation
Property Owner Mailing Address Post Office Box 327				Residential - # of Bedrooms: 0	Design Flow :0 gpd
City St. Helena Site Address/Location 2400 Soda Canyon Road Napa, CA 94558	State CA	Zip 94574	×	Commercial – Type: Winery Sanitary Waste: 150-300 gpd Other:	Process Waste: 500-750 gpd
				Sanitary Waste: gpd	Process Waste: gpd

Company Name Applied Civil Engineering Incorporated	Evaluator's Name Michael R. Muelrath, R.C.E. 67435	Signature (Civil Engineer, R.E.H.S., Geologist, Soil Scientist) Mulau R. Mulautt
Mailing Address: 2074 West Lincoln Avenue		Telephone Number (707) 320-4968
City Napa	State Zip CA 94558	Date Evaluation Conducted November 12, 2009

Primary Area	Expansion Area
Acceptable Soil Depth: 27 to 30 inches Test plt #'s: 9 & 10	Acceptable Soil Depth: 27 to 30 inches Test pit #s: 9 & 10
Soil Application Rate (gal. /sq. ft. /day): 0.6	Soil Application Rate (gal. /sq. ft. /day): 0.6
System Type(s) Recommended: Subsurface Drip	System Type(s) Recommended: Subsurface Drip
Slope: <5% Distance to nearest water source: 100+ feet	Slope: <5% Distance to nearest water source: 100+ feet
Hydrometer test performed? No X Yes □ (attach results)	Hydrometer test performed? No X Yes □ (attach results)
Bulk Density test performed? No X Yes □ (attach results)	Bulk Density test performed? No X Yes □ (attach results)
Percolation test performed? No X Yes □ (attach results)	Percolation test performed? No X Yes □ (attach results)
Groundwater Monitoring Performed? No X Yes □ (attach results)	Groundwater Monitoring Performed? No X Yes □ (attach results)

Site constraints/Recommendations:

The property owner is planning to build a new winery on the subject parcel. A subsurface drip type septic system was previously designed and approved for this site however the residence was never constructed and the system was never installed. The purpose of this site evaluation was to see if it is possible to locate any additional area that is acceptable for wastewater disposal.

The limiting condition in each of the areas tested was the presence of >50% rock at a shallow depth. The only two test pits that had acceptable soil conditions were #9 & #10 located near Soda Canyon Road. The primary constraints in this area are the setback from Soda Canyon Road and the well setback.

Test Pit #1

PLEASE PRINT OR TYPE ALL INFORMATION

	orizon Boundam	0/15		1	`	Consistence	y	1 3		i
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-20	G	30-50	CL	MSB	S	VFRB	SS	CF/FM	CF/CM	NONE
20+		>50%				- 1110		0171101	CI /CIVI	NONE

Test Pit #2

Horizon	Darmdoni	0/10 - 1			C	onsistenc	e			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wali	Ped	Wet	Pores	Roots	Mottling
0-12	G	30-50	CL	MSB	SH	FRB	SS	CF/FM	CF/CM	NONE
12+		>50%	-			1110	- 00	0171101	OI /OIVI	INONL

Test Pit #3

Horizon	Boundame	0/10 - 1	-		(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-20	G	0-15	CL	MSB	SH	VFRB	SS	CF/CM	CF/CM	NONE
20+		>50%				1		0170111	0170101	INOINE
								1		

Test Pit #4

Horizon	Boundary	0/ D = = l=	T		(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-18	G	15-30	CL	MSB	S	VFRB	SS	CF/FM	FF/FM	NONE
18+		>50%						017110	1 1 /1 101	TYONE

Test Pit #5

Horizon	Bassadams	0/101-			(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wail	Ped	Wet	Pores	Roots	Mottling
0-20	G	0-15	CL	MSB	S	VFRB	SS	CF/FM	CF/CM /FC	NONE
20+		>50%							,, 0	

Test Pit #6

Horizon	Daniel	0/50				Consistence	ŧ	ì		
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-12	G	0-15	CL	MSB	S	VFRB	SS	CF/CM	CF/CM	NONE
12+		>50%				1110		0170101	OI /OIVI	INONE

Test Pit #7

Horizon		0.00			(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-20	G	0-15	CL	G	S	VFRB	SS	CF	CF/CM/ FC	NONE
20+		>50%								

Test Pit #8

Horizon		04.50			(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-18	G	30-50	CL	G	S	VFRB	SS	CF/FM	CF/FM	NONE
18+		>50%						3,,,,,,,,	8	
		<u> </u>								

Test Pit #9

Horizon		0/5			(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-27	G	0-15	CL	MSB	S	VFRB	SS	CF/CM	FF/FM	NONE
27+		>50%								1
271		20076				-				-

Test Pit #10

Horizon		0.5	_		(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-30	G	0-15	CL	MSB	S	VFRB	SS	CF/CM	FF/FM	NONE
30+		>50%		T						

Test Pit #11

Horizon			_		(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-12	G	0-15	CL	MSB	S	VFRB	SS	CF/CM	CF/CM	NONE
12+		>50%								
		1		95						

Test Pit #12

Horizon			_		(Consistenc	е			
Depth (inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-24	G	0-15	CL	MSB	S	VFRB	SS	CF/FM	CF/FM	NONE
24+		>50%								

Note: Ground slope = 30% +

Test Pit #13

Horizon					(Consistenc	е			
Depth (Inches)	Boundary	%Rock	Texture	Structure	Side Wall	Ped	Wet	Pores	Roots	Mottling
0-12	G	0-15	CL	MSB	S	VFRB	SS	CF/FM	CF/FM	NONE
12+		>50%							0.7.11	HOILE
12+		>50%								+

Test Pit #14


Horizon Depth (Inches)	Boundary	%Rock	Texture	Structure	Consistence					
					Side Wall	Ped	Wet	Pores	Roots	Mottling
0-14	G	0-15	CL	MSB	S	VFRB	SS	CF/FM	CF/FM	NONE
14+		>50%						0.7	017111	1101112

LEGEND

Boundary	Texture	Structure		Consistence		Pores	Roots	Mottling
A=Abrupt <1"	S=Sand LS=Loamy	W=Weak M=Moderate	Side Wall	Ped	Wet	Quantity:	Quantity:	Quantity:
C=Clear 1"- 2.5" G=Gradual 2.5"-5" D=Difuse >5"	Sand SL=Sandy Loam SCL=Sandy Clay Loam SC=Sandy Clay CL=Clay Loam L=Loam C=Clay SiC=Silty Clay Loam SiL=Silt Loam Si=Silt	S=Strong G=Granular PI=Platy Pr=Prismatic C=Columnar B=Blocky AB=Angular Blocky SB=Subangular Blocky M=Massive SG=Single Grain CEM=Cemented	L=Loose S=Soft SH=Slightly Hard H=Hard VH=Very Hard ExH=Extremely Hard	L=Loose VFRB=Very Friable FRB=Friable F=Firm VF=Very Firm ExF=Extremely Firm	NS=NonSticky SS=Slightly Sticky S=Sticky VS=Very Sticky NP=NonPlastic SP=Slightly Plastic P=Plastic VP=Very Plastic	F=Few C=Common M=Many Size: VF=Very Fine F=Fine M=Medium C=Coarse VC=Very Coarse	F=Few C=Common M=Many Size: F=Fine M=Medium C=Coarse VC=Very Coarse ExC=Extremely Coarse	F=Few C=Common M=Many Size: F=Fine M=Medium C=Coarse Contrast: Ft=Faint D=Distinct P=Prominent

Notes

Structure is recorded as Modifier then Structure - for example, Moderate (M) Subangular Blocky (SB) is recorded as MSB Pores and Roots are recorded as Quantity then Size – for example Few (F) Coarse (C) is recorded as FC Mottling is recorded as Quantity then Size then Contrast – for example Few (F) Coarse (C) Distinct (D) is recorded as FCD





Napa County Department of Environmental Management CUPA-Related Business Activities Form

Business Name: Relic Winery							
Business Address: PO 327, St Helena, CA 94574							
Contact: Schatzi Throckmorton Phone #: 707-967-9380							
A. HAZARDOUS MATERIALS Have on site (for any purpose) hazardous materials at or above 55 gallons for liquids, 500 pounds for solids, or 200 cubic feet for compressed gases (include liquids in AST's and UST's or handle radiological materials in quantities for which an emergency plan is required pursuant to 10 CFR Parts 30, 40 or 70?	□ YES	DS NO					
B. UNDERGROUND STORAGE TANKS (UST's) 1. Own or operate underground storage tanks? 2. Intend to upgrade existing or install new UST's?	U YES	E NO					
C. ABOVE GROUND STORAGE TANKS (AST's) Own or operate AST's above these thresholds: -Any tank capacity with a capacity greater than 660 gallons, or -The total capacity for the facility is greater than 1,320 gallons?	□ YES	ON E					
 D. HAZARDOUS WASTE 1. Generate hazardous waste? 2. Recycle more than 220 lbs/month of excluded or exempted recyclable materials (per H&SC §25143.2)? 3. Treat hazardous waste on site? 4. Treatment subject to financial assurance requirements (for Permit by Rule and Conditional Authorization)? 5. Consolidate hazardous waste generated at a remote site? 	□ YES □ YES □ YES □ YES	G NO E NO E NO E NO					
 Does the business activity include car/fleet washing, mobile detailing, auto-body related activities? Does the business handle Extremely Hazardous Substances in amounts that would qualify for the Risk Management Program? Some examples and their thresholds common to Napa County include: Amunonia – 500 lbs, Sulfur Dioxide – 500 lbs, Chlorine – 500 lbs. 	□ YES	EX NO					

Business Activity.doc (1/99)-1/2

Hev. 2/02

Hornisher, Trish

UPHILLSEPTIC Page 1 of CAVE CLEAR ANCE

From:

Mike Muelrath [Mike@appliedcivil.com]

Sent:

Thursday, July 15, 2010 6:46 AM

To:

Withrow, Kim

Cc:

Hornisher, Trish; Jon Webb; Michael Hirby; Schatzi Throckmorton

Subject:

Relic Winery - Uphill Septic System

Attachments: 2444 Soda Canyon Road Septic - Doug Rowser Letter Regarding Septic History.pdf

Hi Kim,

Attached is the letter from Doug Rowser, previous owner and builder of the house located at 2444 Soda Canyon Road, confirming that the test pits were in fact excavated where the septic system was installed and that the original test pit map was incorrect.

Please review and let me know if you have any further questions.

Thank you,

Mike

Mike Muelrath, P.E. Principal



2074 West Lincoln Avenue Napa, CA 94558

(707) 320-4968 (Telephone)(707) 320-2395 (Facsimile)

www.appliedcivil.com



July 8, 2010

Job No. 09-124

Doug Rowser 18871 Rocky Trail Lower Lake, CA 95457

Re: 2444 Soda Canyon Road (Napa County APN 032-080-042, formerly 032-080-015)

Dear Mr. Rowser:

Thank you for taking the time to discuss the history of development of the property located at 2444 Soda Canyon Road in Napa, California. I understand that you owned the property and developed a residence on the property in the late 1980's / early 1990's. The purpose of this letter is to confirm my understanding of how the property was developed and to document the actual location of where septic system test pits were excavated and where the septic system was installed because there is an apparent discrepancy in the information contained in the County files. Below is my understanding:

- Test pits were excavated in 1989 by Napa Septic and were observed by Napa County Environmental Management Department
- The "Test Pit Map" dated 9/13/1989 (Attachment A) shows the house site and test pits located incorrectly
- The house site and test pits were actually located on an adjacent parcel and a lot line adjustment was completed to bring the house site and septic site onto your property (then APN 032-080-015)
- The test pits excavated in 1989 were actually located in the same location where the septic system was installed
- The house site and actual septic system locations are accurately reflected on the "As Built" dated 6/9/1994 (Attachment B)

Please review and confirm that this information is correct. In particular we are trying to establish that the test pits were excavated in the same location as where the septic system was installed so that we can determine the appropriate setback for a new cave on an adjoining property.

Please feel free to contact me if you have any questions or need me to clarify anything outlined above. If this information is correct we would appreciate your acknowledgement by signing in the space provided below. We will then file this letter with Napa County so that their files have the correct information.

Thank you again for your assistance in clarifying this information.

Sincerely,

Michael R. Muelrath, P.E.

Milas R. Mulnith

Principal

Enclosures:


Attachment A "Test Pit Map" Attachment B "As Built"

The information described in this letter correctly describes the location of the test pits and septic system to the best of my knowledge:

Doug Rowser

Date

7-12-2010



728 I

ZORKA ASTEN (APN 32-030-03) DOUGLAS ROWSER (APN 32-080-FOR A LOT LINE ADJUSTMENT TENTATIVE MAP OF THE LANDS OF DIA

RECEIVED.

JUN 9 1994

ENVIRONMENTAL MANAGEMENT

EGEND

ROWSER 1804c.

±2240

ASTEN \$76.5 Ac

This instruction of the · 一方以及二年 內方

County of Napa

13018EN

745

· 58512

± 3021

SEPTIC AS-BUSLT - 61911994

PROPOSED