"H"

Water Availability Analysis

WATER AVAILABILITY ANALYSIS

Raymond Vineyards

Napa, California APN 030-270-012 & 030-270-013 & 030-050-31



Raymond Vineyards Water Availability Analysis September 15, 2015 Revised January 26, 2016

TABLE OF CONTENTS

PROJECT SUMMARYProject Summary and the s	3
SITE DESCRIPTION	
WATER DEMAND	4
EXISTING WATER DEMAND	4
PROPOSED WATER DEMAND	4
WINERY PROCESS WATER DEMAND	4
DOMESTIC WATER DEMAND	5
IRRIGATION WATER DEMAND	ε
TOTAL WATER DEMAND	
WATER AVAILABILITY	<u>S</u>
DROUGHT CONSERVATION	10
CONCLUSION	10

LIST OF ENCLOSURES

Enclosure A: Overall Site Plan

Ticen Parcel Landscape Site Plan

Enclosure B: Existing Sanitary Sewer and Process Wastewater Generation

Proposed Sanitary Sewer and Process Wastewater Generation

Water Demand Comparison

Enclosure C: Well Log

PROJECT SUMMARY

Boisset Family Estates (BFE) is applying for Use Permit Modification for the Raymond Vineyards winery facility located at 849 Zinfandel Lane, near the town of St. Helena (APN 030-270-013). BFE intends to merge the Raymond Vineyards and Cellar parcel with the adjacent Ticen parcel (APN 030-270-012). The Use Permit Modification involves the conversion of various existing buildings within the Ticen parcel to accommodate hospitality services (e.g. conversion of the existing residence to a private tasting venue with kitchen) as well as modifications within the Raymond Vineyards and Cellar parcel to provide additional parking spaces. In addition to the conversion of existing buildings, the proposed modification will also include an increase in employees. No change in wine production or visitation is requested. Summit has prepared the following Water Availability Analysis, which provides a comparison between the proposed water use and the estimated available water capacity on the property.

SITE DESCRIPTION

Raymond Vineyards is made up of two parcels. The parcel with the winery (APN 030-270-013) has a total of 60.2 acres with 37.7 acres of vineyard. The existing winery facility consists of offices, tasting and winery production buildings. The facility is located in an agricultural area with vineyards to the north, west and south and east. Zinfandel Lane runs parallel with the northern edge of the property. The second Raymond Vineyards parcel (APN 030-050-031) has a total of 27.7 acres with 25.8 acres of vineyard. The Ticen parcel (APN 030-270-012) has a total of 25.5 acres with 20.7 acres of vineyard and an existing residence, barn and shed building.

Water sources for the property consist of four wells, one on the Raymond Vineyards and Cellar winery parcel, one well on the adjacent Raymond Vineyard parcel, and two wells on the Ticen parcel. Well 01, located on the Raymond Vineyards and Cellar parcel (APN 030-270-013), supplies all domestic and process water for the winery. Well 02, located on the adjacent Raymond Vineyard parcel (APN 030-050-031), supplies vineyard irrigation water for the Raymond parcels. Well 03 located on the Ticen parcel (APN 030-270-012), is used for landscape and vineyard irrigation within the current Ticen parcel. Well 04 located on the Ticen parcel (APN 030-270-012), is not operable.

Treated process wastewater, stored in the existing wastewater ponds on the Raymond Vineyards and Cellar parcel, is reused as vineyard irrigation water to complement irrigation supply from Well 02 on the Raymond parcel. Sanitary sewage is and will continue to be disposed of in a separate disposal system.

Refer to the Overall Site Plan attached for a general layout of the project components. These plans also include approximate property boundaries, existing buildings and agricultural development.

WATER DEMAND

EXISTING WATER DEMAND

Current water use at the facility is based on the following needs:

- Process needs for the production capacity of 750,000 gallons per year (for a 3 year average) with a peak of 950,000 gallons per year.
- Employees = 26 per day
- Tasting Visitors = 400 maximum per day
- Deliveries = 5 per day
- Irrigation of 37.7 and 25.8 acres of vineyard within the Raymond parcels
- Irrigation of 3.2 acres of landscape within the Raymond parcel and 0.6 acres within the Ticen parcel
- Frost protection for vineyard

PROPOSED WATER DEMAND

Water use at the facility will be based on the following needs:

- Process needs for the production capacity of 750,000 gallons per year (for a 3 year average) with a peak of 950,000 gallons per year.
- Full Time Employees = 70 per day
- Part Time Employees = 10 per day
- Seasonal Employees (Harvest) = 10 per day
- Tasting Visitors = 400 maximum per day
- Event Visitors
 - o 24 events per year with up to 100 persons
 - o 104 events per year with up to 30 persons
 - o 365 events per year with up to 10 persons
- Irrigation of 37.7 and 25.8 acres of vineyard within the Raymond parcels, and 20.7 acres of vineyard within the Ticen parcels
- Irrigation of 3.2 acres of landscape within the Raymond parcel and 0.63 acres within the Ticen parcel.
- Frost protection for vineyard

WINERY PROCESS WATER DEMAND

Water demand for wine production is expected to correlate to the process wastewater (PW) generated at the facility. The winery production capacity is currently 750,000 gallons per year (for a 3 year average) with a peak of 950,000 gallons per year. No production increase is proposed with this UP modification. Based on typical flow data from wineries of similar size and characteristics, the approximate process wastewater generation for the current wine production is calculated as follows:

Project No. 2015074

Proposed Annual production	=	750,000 gal wine/year
PW generation rate	=	6 gal PW/gal wine ^a
Annual PW Flow	=	750,000 gal wine x 6 gal PW/gal wine
	=	4,500,000 gal PW/year
Average PW Flow	=	(4,500,000 gal PW/year) / (365 days)
	=	12,330 gal PW/day
Peak PW Flow	=	(4,500,000 gal PW/year x 16.4 ^b %)/(30 day)
	=	24,600 gal PW/day
Annual Production Water Demand	=	(4,500,000 gal water/yr) / (325,851 gal/ac-ft)
	=	13.8 ac-ft. water/year

^a Generation rate based on industry standards and water data for similar wineries

Process wastewater generation is expected to be equivalent to the water demand for production. The expected annual water use associated with the average production capacity is 4,500,000 gallons of water per year, or 13.8 ac-ft. /yr. Winery process water demand will continue to be provided by Well 01. See Enclosure B for flows estimates and water demand calculation.

DOMESTIC WATER DEMAND

Domestic water use at the facility is determined based on the total number of employees, daily visitors and event guests. Using Napa County Environmental Management's Table 4 from "Regulations for Design, Construction, and Installation of Alternative Sewage Treatment Systems", the existing annual domestic water usage is estimated as follows:

Table 1. Existing Domestic Water Use for Raymond Vineyards

	Maximum	Water	Daily	Number of	Annual
Use Type	Quantity	Demand	Demand	Days	Water Use
	(persons/day)	(gal/person)	(gal/day)	(days/year)	(gal/year)
Employee	26	20 ^b	520	365	189,800
Tasting Visitors ^a	400	3	1,200	365	438,000
Deliveries	5	5	25	365	9,125
			To	tal Water Use	636,925
			Peak Wa	ter Use (gpd) ^c	1,745
		Т	otal Water U	se (ac-ft. /yr.)	2.0

^a Peak tasting is assumed to occur every day of the year to be conservative.

^b Percentage of flows accounted during the harvest month of September, based on water data for similar wineries

^b Demand per person based on sanitary system design by Mahorney and Associates, see Enclosure B

^c Peak water use based on existing sanitary system disposal capacity.

Raymond Vineyards Water Availability Analysis September 15, 2015 Revised January 26, 2016

Current sanitary sewage generation is expected to be equivalent to the water demand for domestic uses. The current annual domestic water use is 636,925 gallons per year, or 2.0 ac-ft. per year. Domestic water demand is currently provided by Well 01. See Enclosure B for flows estimates and water demand calculation.

Table 2. Proposed Domestic Water Use for Raymond Vineyards

	Maximum	Water	Daily	Number of	Annual
Use Type	Quantity	Demand	Demand	Days	Water Use
	(persons/day)	(gal/person)	(gal/day)	(days/year)	(gal/year)
FT Employee	70	15	1,050	365	383,250
PT Employee	10	15	150	365	54,750
Seasonal Employee (Harvest)	10	15	150	120	18,000
Tasting Visitors ^a	400	3	1,200	365	438,000
Event Visitors	100	15	1,500	24	36,000
Event Visitors	30	15	450	104	46,800
Event Visitors	10	15	150	365	54,750
			To	tal Water Use	1,031,550
			Average Wa	ater use (gpd)	2,830
			Peak Wat	er Use (gpd) ^b	4,050
		1	otal Water U	se (ac-ft. /yr.)	3.2

^a Peak tasting is assumed to occur every day of the year to be conservative

Sanitary Sewage generation is expected to be equivalent to the water demand for domestic uses. The expected annual domestic water use for the proposed marketing and visitation plan is 1,031,550 gallons per year, or 3.2 ac-ft. per year. Domestic water demand will continue to be provided by Well 01. See Enclosure B for flows estimates and water demand calculation.

IRRIGATION WATER DEMAND

Vineyard Irrigation

Water from Well 02 and from the treated wastewater ponds is used to irrigate 37.7 acres of vineyards within the Raymond Vineyards & Cellar winery parcel and 25.8 acres of vineyards within the adjacent Raymond vineyard parcel. The facility used approximately 10,201,854 gallons (31.3 ac-ft. /yr.) for drip irrigation of the vineyard on the Raymond parcels in 2011. It is assumed that the current annual water demand for irrigation and has not changed since 2011, as vineyard acreage remains the same. For comparison, vineyard irrigation annual demand was estimated using a rate of 0.5 ac-ft. per acre of vineyard. Napa County Phase 1 Water Availability Analysis water use guidelines for vineyard irrigation are 0.2 to 0.5 ac-ft./acre/year.

37.7 acres x 0.5 ac-ft./acre/year = 18.9 ac-ft./yr.

25.8 acres x 0.5 ac-ft./acre/year = 12.9 ac-ft./yr.

^b Peak water use is based on the peak sanitary sewage generation which includes employees, tasting visitors, and marketing event visitor's flows.

Total estimated vineyard irrigation demand = 31.8 ac-ft. /yr.

The projected vineyard irrigation demand for the Raymond parcels is based on the most conservative approach, which is the estimated 31.8 ac-ft. per year of water demand.

Water from Well 03 is used to irrigate 20.7 acres of vineyards in the Ticen parcel. The irrigation water demand for the Ticen parcel is estimated using a rate of 0.5 ac-ft. per acre of vineyard.

Vineyard irrigation will typically begin in June when onsite soils begin to dry and continue until October, with the peak irrigation period between July and August. All vineyard irrigation water, other than what is supplied by reclaimed process wastewater, will be supplied by the irrigation Well 02 that is located on the adjacent Raymond parcel (APN 030-050-031) and by Well 03 located on the Ticen parcel.

Landscape Irrigation

The water demand for landscape irrigation was based on the California Department of Water Resources guidelines for Estimated Total Water Use (ETWU) per year:

$$ETWU = (ETo)(0.62)\left(\frac{PF \times HA}{IE} + SLA\right)$$

Where:

ETWU = Estimated Total Water Use per year (gallons)

ETo = Reference Evapotranspiration (inches)

PF = Plant Factor from WUCOLS (see Section 491)

HA = Hydrozone Area [high, medium, and low water use areas] (square feet)

SLA = Special Landscape Area (square feet)

0.62 = Conversion Factor

IE = Irrigation Efficiency (minimum 0.71)

Assumptions:

- Low water use plant types with a plant factor of 0.3 (yarrow, buckbrush, redbud, etc.)
- o High water use plant types with a plant factor of 0.9 (grass)
- o Napa reference evapotranspiration of 49.4 per CIMIS, 1999
- o Irrigation efficiency of 90% for drip systems or similar

The Raymond parcel has approximately 3.2 acres (139,392 SF) of existing landscape which consists of grass (turf) and a biodynamic garden with a herbarium and other trees. In our previous WAA, we had indicated a proposed increase in landscape in the Raymond parcel. After further revisions of the landscaping plan it was determined that no additional landscape is proposed for the Raymond parcel. Landscape will continue to be irrigated with water from wells 01 and 02. A conservative plant factor of 0.9 will be used for existing landscaping.

Raymond Vineyards Water Availability Analysis September 15, 2015 Revised January 26, 2016

ETWU (existing) =
$$(49.4 \text{ in/year}) (0.62) (0.9*139,392 \text{ SF}) = 4,269,298 \text{ gal/yr.} = 13.1 \text{ ac-ft./yr.}$$

0.9

The Ticen parcel has approximately 0.6 acres (26,136 SF) of existing landscaping and propose to add 2,498 SF of additional landscape consisting of low water use plant types such as yarrow, buckbrush, redbud, etc. (see Enclosure A for Landscape Plan). The proposed total acreage of landscape for the Ticen parcel is 0.66 ac (28,634 SF). Landscape will continue to be irrigated with water from well 03. A conservative plant factor of 0.9 will be used for existing landscape and a plant factor of 0.3 will be used for the proposed new landscape.

ETWU (existing) =
$$(49.4 \text{ in/year}) (0.62) (0.9*26,136 \text{ SF}) = 800,493 \text{ gal/yr.} = 2.5 \text{ ac-ft./yr.} 0.9$$

ETWU (additional) = $(49.4 \text{ in/year}) (0.62) (0.3*2,498 \text{ SF}) = 25,503 \text{ gal/yr.} = 0.1 \text{ ac-ft./yr.} 0.9$
ETWU (total) = $2.5 \text{ ac-ft./yr.} + 0.1 \text{ ac-ft./yr.} = 2.6 \text{ ac-ft./yr.}$

Frost Protection Water usage

Water from well 02 and the treated wastewater ponds is used for frost protection of vineyards on the Raymond parcels. In our previous WAA, we had indicated a projected frost protection water demand of 47.7 ac-ft. per year. In further follow-up with the facility, this demand was an estimate based on assumed hours of sprinkler operation. Since this estimate is not based on actual data we have revised this analysis to reflect a rate of 0.25 ac-ft. per acre of vineyard, which is the standard for Napa County Phase 1 Water Availability Analysis water use guidelines for vineyard frost protection.

Total estimated frost protection demand for 63.5 acres of vineyard = 15.9 ac-ft. /yr.

The projected vineyard frost protection water demand for the Raymond parcels is 15.9 ac-ft. per year. Frost protection for the Ticen parcel is provided by a stationary fan.

• Fire Protection Water usage

An existing pond supplies the required water for fire protection. Water demand for fire protection is not included in the total water demand since is not directly provided by any water source.

TOTAL WATER DEMAND

The total water demand at the facility is expected to be 90.8 ac-ft. per year. If vineyard irrigation and frost protection demands for the Raymond parcel are excluded (since these demands are provided by Well 02 on the adjacent Raymond parcel) the annual water demand for the winery parcel is 32.7 ac-ft. per year. Some of the required vineyard irrigation water demand will also be supplied by treated process wastewater and will offset the amount of irrigation well water required.

Table 3. Total Proposed Annual Water Demand

Water Use	Peak Gallons per day	Gallons per year	Acre-Feet per year			
Wine Production	24,600	4,500,000	13.8			
Domestic Use	4,050	1,032,000	3.2			
Vineyard Irrigation ^c	51,000 ^a	13,751,000	42.2			
Landscape Irrigation	19,000 ^a	5,116,000	15.7			
Frost Protection ^d	172,700 ^b	5,181,000	15.9			
Total	90.8					
Total Water Demand req	32.7					
Total Water Demand required/provided by irrigation wells 58.1						

^a Estimated assuming 9 months of irrigation (no irrigation during winter)

WATER AVAILABILITY

Based on the Water Availability Analysis method for allotted water use for Napa Valley Floor Areas (1 ac-ft/acre/year), the Raymond Vineyards & Cellar parcel would be allotted 60.2 ac-ft /yr, the Raymond Vineyard parcel would be allotted 27.7 ac-ft/yr, and the Ticen parcel would be allotted 25.5 ac-ft/yr; therefore, the total allotted water use for all three parcels would be 113.4 ac-ft /year. The estimated water demand for process, domestic, and landscape uses of 32.7 ac-ft /year represents 29% of the water available. Based on the proposed increase in employee, visitation, and landscape acreage, there will be an overall increase in projected water demand of about 1.3 ac-ft/year (see Table 4).

Table 4. Water Availability

Parcel & Uses	Parcel Size (acres)	Water Allotment (ac-ft./year)	Existing Demand (ac-ft./year)	Proposed Demand (ac-ft./year)	Water Source Parcel
030-270-012	25.5	25.5			
030-270-013	60.2	60.2			
030-050-031	27.7	27.7			
Wine Production			13.8	13.8	030-027-013
Domestic Use			2.0	3.2	030-027-013
Vineyard Irrigation			42.2	42.2	030-050-031 & 030-270-012
Landscape Irrigation			15.6	15.7	030-027-012 & 030-027-013
Frost Protection			15.9	15.9	030-050-031
TOTAL	113.4	113.4	89.5	90.8	

There are 3 wells that are currently used for water supply for the Raymond and Ticen parcels, as indicated on the attached Site Plan (Enclosure A):

^b Estimated assuming 30 days of frost season

^c Water for vineyard irrigation is provided by Ticen wells and offsite Raymond well

^d Frost protection water is provided by offsite well and treated wastewater pond

Raymond Vineyards Water Availability Analysis September 15, 2015 Revised January 26, 2016

Well 01 was drilled in 1978 to a depth of 410 feet, and has a 20 ft. annular seal. The existing domestic well yields approximately 100-120 gpm. There has been no evidence of groundwater depletion. The peak domestic water demand should account for 24,600 gal/day of process water and 4,050 gal/day of domestic water, for a total of 28,650 gal/day. Well 01 would need to supply approximately 60 gpm over 8 hours to meet the potable water demand, and should have sufficient capacity to meet the peak domestic water demand (see attached well log in Enclosure C).

Well 02, located on the adjacent Raymond parcel (APN 030-050-031), has a capacity of 60 gpm and is sufficient to supply all irrigation water demand for the Raymond parcels.

Well 03, drilled in 2006 and located on the Ticen parcel (APN 030-270-012), has a capacity of 40 gpm and is sufficient to provide irrigation demands for the Ticen parcel.

Well 04, drilled in 1984 and located on the Ticen parcel (APN 030-270-012), has a capacity of 12 gpm, but is currently non-operable.

DROUGHT CONSERVATION

The facility plans to continue to treat the process wastewater generated at the facility and reuse it for vineyard irrigation purposes, offsetting the water demand for irrigation uses. Domestic wastewater will be treated and disposed of in a subsurface system, recharging the groundwater table through infiltration.

CONCLUSION

Total annual water demand at Raymond Vineyards and Ticen for process, domestic and landscape uses is projected to be 32.7 acre-feet, which is below the allowable water allotment of 113.4 acre-feet (90.8 ac-ft. with vineyard irrigation and frost protection included). The anticipated peak daily potable water demand for the parcel can be met with the existing potable water supply (well 01) operating for 8 hours per day at 60 gpm.

Contact: Gina Giacone gina@summit-sr.com (707) 636-9162



SUMMIT ENGINEERING, INC. 463 Aviation Blvd., Suite 200 Santa Rosa, CA 95403 707 527-0775 sfo@summit-sr.com


SUMMIT ENGINEERING, INC. Project No. 2015074


ENCLOSURE A

OVERALL SITE PLAN

LANDSCAPE PLAN







ENCLOSURE B EXISTING AND PROPOSED WATER DEMAND

ENCLOSURE C



SUMMIT ENGINEERING, INC.	RAYMOND VINEYARDS & CELLAR Wastewater Feasibility Study Process Wastewater Flows	PROJECT NO. BY: CHK:	2015074 GG
PROCESS WASTEWATER			
Annual Volume			

Annual Production (projected) 750,000 gal wine/year

Generation Rate (assumed)^a 165 gal wine/ton grapes

Tons Crushed 750,000 gal wine/year 165 gal wine/ton grapes = 4,545 tons grapes/year

Process Wastewater (PW) Generation Rateb (assumed) 6.00 gal PW/gal wine

Annual PW Flow 750,000 gal wine/year 6.00 gal PW/gal wine 4,500,000 gal PW/year

Average Day Flow

4,500,000 gal PW/year 365 days 12,329 gal PW/day

Napa County Peak Day Flow

Length of Harvest 60 days

750,000 gal wine/year 60 days Peak Flow 1.5 18,750 gal PW/day

Average Day Peak Harvest Month Flow

16.400% of the PW flows are accounted for during October Assume:

2 30 days in October

Peak Flow 4,500,000 gal PW/year 16.4% 24,600 gal PW/day

30 days

24,600 gal PW/day

SUMMIT ENGINEERING, INC.	RAYMOND VINEYARDS & CELLAR	PROJECT NO.	2015074
·	Wastewater Feasiblity Study	BY:	CL
	Sanitary Sewage Flows	CHK:	GG
	, -		

SANITARY SEWAGE

DESIGN FLOW

WINERY

Non-Harvest Peak Tasting w	ı/o Event				
Employee (full-time)	70 x	15 gpcd	=	1,050 gal/day	
Employee (part-time)	10 x	15 gpcd	=	150 gal/day	
Employee (seasonal)	0 x	15 gpcd	=	0 gal/day	
Public Tasting Visitors	400 x	3 gpcd	=	1,200 gal/day	
Private Tasting Visitors	0 x	3 gpcd	=	0 gal/day	
Peak Event (catered)	0 x	15 gpcd	=	0 gal/day	
Total			=	2,400 gal/day	
Harvest Peak Tasting w/o Ev	<u>vent</u>				
Employee (full-time)	70 x	15 gpcd	=	1,050 gal/day	
Employee (part-time)	10 x	15 gpcd	=	150 gal/day	
Employee (seasonal)	10 x	15 gpcd	=	150 gal/day	
Public Tasting Visitors	400 x	3 gpcd	=	1,200 gal/day	
Private Tasting Visitors	0 x	3 gpcd	=	0 gal/day	
Peak Event (catered)	0 x	15 gpcd	=	0 gal/day	
Total			=	2,550 gal/day	Average Domestic Water Demand during
					Peak Period (w/out event)
Non-Harvest Peak Tasting w					
Employee (full-time)	70 x	15 gpcd	=	1,050 gal/day	
Employee (part-time)	10 x	15 gpcd	=	150 gal/day	
Employee (seasonal)	0 x	15 gpcd	=	0 gal/day	
Public Tasting Visitors	400 x	3 gpcd	=	1,200 gal/day	
Private Tasting Visitors	0 x	3 gpcd	=	0 gal/day	
Peak Event (catered)	100 x	15 gpcd	=	<u>1500</u> gal/day	
Total			=	3,900 gal/day	
Harvest Peak Tasting w/ Eve	<u>ent</u>				
Employee (full-time)	70 x	15 gpcd	=	1,050 gal/day	
Employee (part-time)	10 x	15 gpcd	=	150 gal/day	
Employee (seasonal)	10 x	15 gpcd	=	150 gal/day	
Public Tasting Visitors	400 x	3 gpcd	=	1,200 gal/day	
Private Tasting Visitors	0 x	3 gpcd	=	0 gal/day	
Peak Event (catered)	100 x	15 gpcd	=	1500 gal/day	
Total			=	4,050 gal/day	

^{*}portable toilets will be used for larger events greater than 150 persons

4,050 gal/day

SUMMIT ENGINEERING, INC.
Project No. 2015074

WELL LOG



DUPLICATE Driller's Copy

THE RESOURCES AGENCY DEPARTMENT OF WATER RESOURCES WATER WELL DRILLERS REPORT

Do not fill in

No. 103316

Local Permit No. or Date	Ollier Well No.
(1) OWNER: Name Raymond Vineyards	
Address 849 Zinfandel Lane	(12) WELL LOG: Total depth. 2.10ft. Depth of completed well 10_ft.
	from it, to it, committee (Describe by color, character, size or material)
	0 -4 Soil
(2) LOCATION OF WELL (See instructions): County Napa Owner's Wall Numi 0-270-03	4 -27 Clay gravel imb
County Napa Owner's Wall Numb3-0-270-03	27 -38 Cemented gravel
Well address if different from aboveSame	38 -83 clay gravel imb
Township	The second secon
Distance from cities, mads, milmads, fences, etc.	
south o from cines, water, minings, sences, etc.	
The state of the s	96 -118 Blue clay gravel imb
The state of the s	118 -139 Brown\sandy clay & graved
	139 -143 Cemented gravel
(3) TYPE OF WORK:	143 /183 Blue clay
New Well 20 Deepening [183 225 Brown clay gravel imb
Reconstruction	225 252 Cemented gravel
Reconditioning	7
(Ongeler Way)	Party of Player
flurizontal Well	351 Sandy brown clay
Destruction in (Describe destruction materials and procedures in Item 12)	201387 Comented gravel
procedures in Item 12	187 -198 Gravel small poulders & gray sa
(4) PROPOSED USE	caay
Domustic	7 198 ALOSEICKY DIGWIT CLAY
Irrigation	A Thomas Carry
	11/2
Rent Well	
Stock	(1) - 0(10
NEST. HELENAHUY / Municipal)	
WELL LOCATION SKETCH Other	0
(5) EQUIPMENT: (6) GRAVED PACK:	
Cable Air Playtetor of bone 1815	
Other Bricket Rockets from 20 to 410 to	
7) CASING INSTALLED (8) PERFORATIONS TO China	
iteel D Plastic C Characte Type of pentinglian or size of screep	
1/	
From To Dia Gareor From To Silon ft. Wall ft.	
	the material to the state of th
0 90 ND8 188 90 410 N7/8x3	
	- ·
9) WELL SEAL:	Part Control of the C
Was surface sanitary seal provided? Year No 1 If yes, to depth 20 ft.	
Were strata sealed against pollution? Yes No. No. Intervalft.	, P
Method of soaling growth	0/3 70
10) WATER LEVELS:	Work started 8/1 19 78 Completed 8/11 1978
Depth of first nature if houses OTA	WELL DRILLER'S STATEMENT:
landing hard often well	This well was drilled under my jurisdiction and this report is true to the hest of my knowledge and holief.
11) WELL TESTS:	
	Signed (Well Driller)
Vas well test made? Yes Pump No If yes, by whom Pri lers Pump Bailer Air life	
Denth to water at start of test 25 ft. At end of test 100 Fft	NAMEDoshier-Gregson Drilling Inc (Porson, firm, or corporation) (Typed or printed)
rige 100 gal/min after hours Water temperature	Address 5365 Napa Vallejo Huy
	CityVallejo z _{Ip} 94590
22	A 4-1 4 A
vas electric log ninde? Yes [] No [] If yes, attach copy to this report	License No. 291,001 Date of this report 8/14/78

TRIPLICATE
Retain this copy

WATER WELL DRILLERS REPORT

(Sections 7079, 7080, 7081, 7082, Water Code)

THE RESOURCES AGENCY OF CALIFORNIA DEPARTMENT OF WATER RESOURCES

Do Not Fill In

Nº 12845

-							Other Well No.
(1) 0	WNER:	1					(11) WELL LOG:
Name	TO T AND VIRGINIA						
Address 1459 Kerney Street, St. Helena,						Total depth 302 ft. Depth of completed well 302	
California						Formation: Describe by color, character, size of material, and structure	
(2) LO	CATION						0 - 4 top soil
County Nava Owner's number, if any						300 1700	
Township, Range, and Section						SOLE AGILOW CIAN	
			erc. 3c M	4 20	of Hid wh	200	26 - 38 sand and gravel
Distance from cities, roads, railroads, etc. & Mi. E of Highway 29 & Mi. so. of Zinfandel Lane						38 - 60 soft yellow clay	
(3) TY	PE OF V	VORK	(chech) •	ASSAAGE	·	60 - 62 clay
New Well	10	ening [ditioning [] Destroyi	[7	62 - 68 gravely clay
If destruct	ion, describe		and proced	ure in Item	Destroy1	ıığ ∐	70 - 79 sand and gravel
	OPOSED					IPMENT:	STATE OF THE STATE
Domestic	: 🔲 Indu	strial [7 Munic	inal [everse	3.44.44
Irrigation	n 🗶 Test	Well		ther	Cable	SAGE 200	90 - 110 gravel and rocks
	444		_		Other	H	110 - 118 gravel (large)
(6) CA	SING IN	STATI	ED.	T	O ULIOI		118 - 128 blue clay
			-		If gravel pac	ked	128 - 130 blue sand
	EL; Doubt	OTHE F D	ER:	1	- Praver had	Ted	130 - 139 sandy blue clay
	SINGLE TOUBLE				139 - 142 sandy yellow clay		
P	-		Gage	Diameter		1	142 - 150 sand and gravel
From ft.	To ft.	Diam.	or Wall	of Bore	From	To	150 - 155 sand and gravel large
0	-				ft.	ft.	155 - 156 yellow clay
	302	THE TANK	1/4	22"	0	302	156 - 185 blue grey clay
1 3211	1	14"	-				185 - 194 sand and gravel
	blain,	14'	13/16	" pla		vered	/155 - 197 yellow clay
Size of shoe or				Size of grav	rel: 3/	16"	197 - 203 sand and gravel
Describe Joint							203 - 205 blue clay
	FORATI						205 - 207 sand and gravel
Type of perfo	ration or name	of screen	fact	ory 1	ouvered	1	207 - 210 blue gray clay
		100	Perf.	Rows			210 - 219 blue clay
From ft.	To	1	per	per	S .	Size	219 - 226 sand and gravel
	ft.		row	ft.	in.	x in.	226 - 248 rooks and gravel
144	168		Ouver				248 - 254 blue clay
188	198	1	00 81	ot_sc	reen		254 - 263 rocks and gravel
218	242	10	Suver	ed -			263 - 266 blue clay
242	252	10	00 51	ot_sc	raan		266 - 286 rocks and grave
272	292	110	ാര ജി	ot sa	rean	= 44E - 5	266 - 286 rocks and gravel 286 - 300 blue clay
	STRUC:						ass san price cray
Was a surface	sanitary seal pr	ovided? Y	es E No	· 🗆 🗆	To what depth	20 ft.	
ere any strat	a sealed against	pollution?	Yes 🔲	No 🔲	If yes, note o	depth of strata	
rom	ft. to		fe.				
rom	ft, to	1	ft.				Work started 10-14 19 71 , Completed 10-17 19 71
fethod of seali	ing Z	cemer	1¢				WELL DRILLER'S STATEMENT:
	FER LEV		if known		ft.		This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
	before perfora				ft.		NAME Ben Barrow Co.
	after perforati						(Person, firm, or corporation) (Typed or printed)
	LL TEST		- Coping		ft.		
	made? Yes	1.6	1 74	L			Address P. S. Box 388 Woodland, Calif.
ield :	200000000	in. with		yes, by whom?			
emperature of				ft. drawdou		hrs.	[SIGNED]
				analysis made		,	(Well Driller)
the life log	made of well?	Yes []	No 🗆	If yes, at	trach copy		License No. 153008 Dated Oct 25 71