

Sanitary Sewer & Recycled Water Standards

NapaSan Board of Directors Meeting June 17, 2020

NSD Board of Directors Meeting – June 17, 2020



Specifications & Details

- Set requirements for:
 - Development construction
 - Repair/rehabilitation of private systems
 - Modifications to NapaSan facilities by other parties
- Required by NapaSan Code
- Last approved in June 2019



Modifications

- Clarify document to be consistent with current practices
- Typographical / formatting errors



2020 Notable Changes

- -Clarify manhole connection requirements
- Addition of Pre-Rinse Sink to grease requirements
- -Changes to manhole coating rehabilitation requirements

Pre-Rinse Sink Grease Requirements

Fixture	Connect Direct	Connect to Grease
	to Sewer	Interceptor
Pot Sink		X
Prep Sink		X
3-Compartment Sink		X
Pre-Rinse Sink		<u>×</u>
Vegetable Prep Sink	X	
Kitchen Mop Sink		X
Floor Drain (in kitchen)		X
Hand Wash Sink (in kitchen)	X	
Dishwasher		X
Garbage Disposal	X	
Commercial Trash Compactor		X
Trash Enclosure		X
Floor Sink (for beverage dispenser)	X	
Condensate Discharge	X	
Walk-in Cooler Discharge	X	

NapaSan

NapaSan

Manhole Connection Requirements

10.20 CONNECTION TO EXISTING MANHOLE

In existing manholes where no <u>suitable</u> stub exists <u>to extend the main or connect a</u> <u>public lateral</u>, Contractor shall <u>install a new manhole per NapaSan Standards to provide</u> <u>a suitable connection.provide a channel in the portion of the base block located inside</u> the manhole two inches larger than the outside diameter of the proposed stub. It shall be the responsibility of the Contractor to perform all the necessary work on the exterior of the manhole in preparation for the installation of the new stub. The Contractor shall be responsible for the alignment and grade of the new stub. The Contractor shall make a water tight seal of the new stub from the outside of the manhole. All work by the Contractor shall be performed in a manner that will maintain the integrity of the existing manhole. The Contractor shall provide 24 hours' notice to the District prior to the start of any work.



Distribution

- Online at NapaSan website
- Email to distribution list
- Effective date of June 26, 2020



Recommendation

 Approve updates to the Sanitary Sewer and Recycled Water Standards