

# PRELIMINARY STORMWATER RUNOFF MANAGEMENT PLAN (SRMP)

ALLIED CLEAN FUELS TERMINAL PROJECT 221 DEVLIN ROAD NAPA, CALIFORNIA

APN 057-020-033

Prepared For:

Allied Propane Services 221 Devlin Road Napa, CA, 94559 (707) 252-5500

#4113044.0
January 15, 2014

# Allied Clean Fuels Terminal Project Stormwater Runoff Management Plan



# **TABLE OF CONTENTS**

I. PURPOSE	1
II. EXISTING CONDITIONS	1
III. PROPOSED DEVELOPMENT	1
IV. DRAINAGE STUDY	2
V. STORMWATER POLLUTION CONTROL	2
ANTICIPATED ACTIVITIES AND POLLUTANTS	2
RECEIVING WATERS OF CONCERN	3
VI. POST-CONSTRUCTION BMPS	3
SITE DESIGN BMPS	4
SOURCE CONTROL BMPS	4
TREATMENT CONTROL BMPS	6
VII. CONCLUSIONS	6

# **ATTACHMENTS**

- 1) VICINITY MAP, USGS MAP, AERIAL IMAGE (CURRENT SITE PHOTO)
- 2) CIVIL IMPROVEMENT PLANS
- 3) PRE & POST-DEVELOPMENT DRAINAGE STUDY
- 4) NAPA COUNTY CONSTRUCTION APPENDIX A NAPA COUNTY POST-CONSTRUCTION APPENDICES
- 5) TREATMENT CONTROL BMPS
- 6) OWNER'S CERTIFICATION



# Purpose

This report addresses Napa County Stormwater Runoff Management Plan (SRMP) requirements. The project's post-construction stormwater management level is identified as a "Priority Project." The requirements are outlined in the Napa County Post-Construction Runoff Management Requirements, dated June 3, 2008.

This report also addresses Marin Napa Solano Sonoma Stormwater Association compliance requirements. The project is classified as a Tier 2 project. Requirements are outlined in the Model Stormwater Technical Guide Draft for compliance with stormwater post-construction requirements to begin implementation by June 30, 2015. The preliminary design of stormwater treatment facilities and other stormwater pollution control measures in this plan are in accordance with the current edition of the MNSSSA Stormwater Technical Guide.

# II. Existing Conditions

The Allied Clean Fuels Terminal project is located at 221 Devlin Road in Napa, California. The APN is 057-020-033 and the parcel has an area of 6.37 +/- acres. The property currently contains an office building and warehouse along with propane storage facilities for Allied Propane. The site is bounded to the north by Devlin Road and Highway 29, to the west by the existing Allied Propane building and a storage facility beyond, to the east by a recently-approved commercial subdivision project and to the south by vacant land. The eastern side of the parcel is undeveloped and is covered in vegetation. No wells exist on the site.

The property slopes generally southward with 0.5% to 2.5% slopes. A shallow, vegetated flow path bisects the eastern field from north to south. Runoff from the property flows via surface flows to the south before entering a blue line creek and ultimately discharging to Napa River. Refer to Attachment 1 for a Vicinity Map, USGS Site Map, and an Aerial Photo showing the parcel topography, features and boundary.

# III. Proposed Development

The Clean Fuels Facility project is being proposed on the eastern portion of the parcel which currently houses Allied Propane. The facility proposes to supply Compressed Natural Gas (CNG), Liquefied Natural Gas (LNG), Propane (LPG), Diesel Emissions Fuels (DEF), Diesel, and Unleaded Gas for trucks and autos. Four fuel dispensers are proposed at the front of the project for retail gasoline and diesel fuel sales. The facility will also provide additional services for all hybrid environmental flex fuel vehicles. At the rear of the project, a commercial state-of-the-art card lock facility with nine truck fueling islands is proposed to supply all fuel types. Also a four station state-of-the art quick charge electric vehicle charging depot and a 3,312 sf convenient store will be constructed.

Runoff from the proposed project will be directed to bioretention facilities on site. Runoff will then be discharged to natural vegetated flow lines. The proposed project will disturb an area of



approximately 3.2 acres. The volume of soil to be moved during the project will be minimal. Refer to Civil Improvement Plans in Attachment 2, for the overall scope of the project.

# IV. Drainage Study

This is a Priority Project that proposes over 10,000 sq.ft. of new or reconstructed impervious space, so a drainage study is required by the Napa Post-Construction Runoff Management Requirements. This drainage study was performed in compliance with the new Marin Napa Solano Sonoma Stormwater Association Model Stormwater Technical Guide Draft. It requires that the project demonstrate that runoff from impervious area be directed to a bioretention facility, and that the bioretention areas have a surface area equal or greater than 4% of the total tributary area to the bioretention facility.

The project site consists of two drainage management areas. The information about the drainage management areas can be found in the table below (refer to the DMA Map in Attachment 3):

Table 1.

DMA Name	Area (sq. ft)	Post Project Surface Type	Runoff Factor	Receiving self- retaining DMA	Receiving self retaining DMA Area
1	44,389	90% paved	1	N/A	N/A
2	68,522	90% paved	1	N/A	N/A

Table 2.

1	DMA	Area	Post Project	Runoff	DMA Area x			
1	Name	(sq. ft)	surface type	Factor	Runoff Factor			
	1	44,389	90% paved	1	44389			
1		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				IMP Sizing	Minimum	Proposed
Į	2	68,522	90% paved	1	68522	Factor	Area	Area
				Total	112911	0.04	4516.44	5532

The proposed development will have sufficient bioretention area to treat the stormwater runoff to the maximum extent practicable.

# V. Stormwater Pollution Control

# Anticipated Activities and Pollutants

The proposed project construction activities will potentially include the following pollutant sources:

# A. Vehicle fluids



- C. Cement associated with PCC concrete/shotcrete operations
- D. General Litter
- E. Mortar Mix
- F. Treated Lumber
- G. Clearing and Grubbing Operations
- H. Solvent and Adhesives
- I. Paint
- J. Cleaning Chemicals
- K. Grading Operations
- L. Material Stockpiles
- M. Sediments

The potential contaminants of concern based on the potential pollutant sources outlined above are as follows:

- A. Sediments
- B. Nutrients
- C. Trash and Debris
- D. Metals
- E. Total Petroleum Hydrocarbons

# **Receiving Waters of Concern**

Stormwater from the site discharges to natural vegetated flow lines, and eventually drains into the Napa River. According to Appendix F of the Napa County Post-Construction Runoff Management requirements, the potential pollutants of concern developed by this project are:

- 1. Sediment
- 2. Nutrients
- 3. Metals

Stormwater Best Management Practices (BMPs) are implemented to reduce potential pollutants from the proposed uses. The proposed disturbed area exceeds 1 acre. A Storm Water Pollution Prevention Plan will be prepared for the project. A Notice Of Intent will be filed with the San Francisco Regional Water Resources Control Board.

# VI. Post-Construction BMPs

This project is classified as a Priority Project by the Napa County Post-Construction Runoff Management Requirements. As such, appropriate Site Design, Source Control BMPs, and Treatment Control BMPs have been incorporated into this project. The stormwater Best Management Practices (BMPs) listed below are implemented to reduce the post-development



runoff volume and peak runoff rate, and limit pollution generation from the source, prior to discharge off-site.

There are relatively few potential pollution sources associated with the proposed fuel terminal. The primary sources are concentrated flows and driveway/roof runoff. Existing vegetation will be maintained downslope of the project area to treat contaminant laden runoff to the maximum extent practicable (MEP) and the bioretention areas will be used to treat stormwater and mitigate increased flows resulting from increased impervious area. Design and selection of these methods are based upon the California Stormwater Best Management Practices (BMP) Handbook published by the California Stormwater Quality Association (CASQA), and new Napa County Stormwater standards.

# Site Design BMPs

The following BMPs have been implemented to reduce the post-development runoff volume:

- Minimize impervious footprint. The driveways and parking aisles have been designed to the minimum allowable widths.
- Conserve natural areas. Natural drainage systems will be used to the maximum extent practicable.
- Minimize directly connected Impervious Areas. Runoff from the project area will be directed to bioretention, and will be discharged to vegetated flow lines.
- Maximize canopy interception and water conservation. New landscape will be professionally designed to incorporate native or drought tolerant plants and large shrubs in place of non-drought-tolerant species.

# Source Control BMPs

The following BMPs have been implemented to limit pollution generation from the source:

# A. Roads and Driveways

• The surfaces and slopes of new driveways shall comply with the latest version of the Napa County Road and Street Standards.

#### **B. Parking Areas**

 Runoff from parking areas will be directed to bioretention to infiltrate and treat stormwater



# C. New or Reconstructed Stormwater Conveyance Systems

• Ditches and other open conveyance systems shall be lined with vegetation to protect exposed soils and to treat stormwater runoff before being discharged.

# D. Storm Drain Inlets, Open Channels, and Creeks

 Provide concrete stamping, or equivalent, of all stormwater conveyance system inlets and catch basins within the project area with prohibitive language (e.g., " No Dumping-Drains to XXXX River/Creek/Lake"). Signage shall identify the receiving water the drain discharges to and include a message in Spanish.

### E. Landscaping

- Existing native trees, and shrubs shall be preserved to the maximum extent practicable.
- New Landscape will be professionally designed to minimize irrigation, runoff, and the
  use of fertilizers and pesticides that can contribute to stormwater pollution. Plants shall
  be selected as appropriate to the soils, slopes, climate, sun, wind, and other site
  conditions.

### F. Trash Storage Areas

- Trash storage areas shall be paved with an impervious surface and designed not to allow run-on from adjoining areas, and screened or walled to prevent off-site transport of trash.
- All trash containers will have lids that exclude rain.

#### H. Roofs, Gutters, and Downspouts

 All roofs, gutters, and downspouts will consist of protected metals or will drain to landscape.

# P. Fueling Areas

- All fueling areas will be covered with an overhanging roof structure.
- All fuel dispensing areas will be paved with Portland cement concrete (or equivalent smooth impervious surface), and the use of asphalt concrete shall be prohibited.
- All fuel dispensing areas must have a 2% to 4% slope to prevent ponding, and must be separated by a grade break to prevent run-on to the maximum extent practicable.
- Concrete fuel dispensing area will extend 6.5 feet from the corner of each fuel dispenser, or the length at which the hose and nozzle assembly may be operated plus 1 foot whichever is less.
- Above ground fuel tanks must be protected with a secondary containment structure of sufficient volume to contain all of the fuel in the event of a tank rupture.



### **Treatment Control BMPs**

The Allied Clean Fuels Terminal project is classified as a Priority project so Treatment control BMPs are required for this project.

#### 1. Bioretention Facilities

Bioretention areas are landscaping features that are expanded to provide on-site treatment of stormwater runoff. Surface runoff is directed into shallow, landscaped depressions that are designed to infiltrate and treat stormwater runoff. The runoff filters through the mulch and prepared soil mix. The filtered runoff can be collected in a perforated underdrain and returned to the storm drain system.

Routine maintenance is critical to the successful operation of BMPs. General maintenance includes inspection of BMPs at the beginning and end of the wet season, vegetation management, debris and sediment removal, restoration of damaged area in a BMP, and possible vector control.

The applicant accepts responsibility for interim operation and maintenance of stormwater treatment and flow-control facilities until such a time as this responsibility is formally transferred to a subsequent owner. The owner shall execute a Maintenance and Operation Agreement with the County of Napa.

#### VII. Conclusions


The stormwater runoff management plan outlined above is incorporated into the design of the proposed Allied Clean Fuels Terminal project. This plan demonstrates that appropriate, site specific best management practices will be implemented to minimize contaminant laden runoff from leaving the parcel. With the implementation and proper maintenance of stormwater treatment controls, the proposed project can control the runoff volume, flow rate and treatment of contaminant laden runoff.



# **ATTACHMENT 1**


Vicinity Map, USGS Map, Aerial Image (Current Site Photo)


# ALLIED CLEAN FUELS TERMINAL VICINITY MAP CALIFORNIA



NOT TO SCALE










# **ATTACHMENT 2**

**Civil Improvement Plans** 

PROPERED IN THE PROPERTY OF TH ALLIED C EXISTING ALLIED PLANS FOR TERMINAL ROAD RE DECISIONES SON ON ROLE FLAN HAS COMPLES FROM A PRED SAMES DOME SETTEMBER 200 ET RECUERS SERVEZ A ASSOCIATES PRITY BINDE BRUICE TO NUMBERON BY PLOCO METRI DOCS NOT LE HITEM THE KICHTEMP PLOCOPLAN PRELIMINARY NOT FOR CONSTRUCTION ASPORTATION AND HAND HAND HE ALLIED CLEAN FUELS TERMINAL COVERSHEET RIECHERS SPENCE





# **ATTACHMENT 3**

**Drainage Study** 

# TERMINAL AREA CLEAN FUELS T MANAGEMENT NAPA CALIFORNIA ALLIED DRAINAGE




Table 1.

DMA Name	Area (sq. ft)	Post Project Surface Type	Runoff Factor	Receiving self- retaining DMA	Receiving self retaining DMA Area
1	44,389	90% paved	1	N/A	N/A
2	68,522	90% paved	1	N/A	N/A

Table 2.

rable 2.							
DMA	Area	Post Project	Runoff	DMA Area x			
Name	(sq. ft)	surface type	Factor	Runoff Factor			
	44,38						
1	9	90% paved	1	44389			
					IMP		
	68,52				Sizing	Minimu	Propose
2	2	90% paved	1	68522	Factor	m Area	d Area
			Total	112911	0.04	4516.44	5532



# **ATTACHMENT 4**

Napa County Construction Appendix A Napa County Post-Construction Appendices

# NAPA COUNTY CONSTRUCTION SITE RUNOFF CONTROL REQUIREMENTS APPENDIX A – PROJECT APPLICABILITY CHECKLIST

# Construction Site Runoff Control Applicability Checklist

County of Napa Department of Public Works 1195 Third Street, Suite 201 Napa, CA 94559 (707) 253-4351 www.co.napa.ca.us/publicworks



Project Address:

221 Devlin Road Napa, CA 94558 Assessor Parcel Number(s): 057-020-033

Project Number: (for County use Only)

#### INSTRUCTIONS

Structural projects that require a building and/or grading permit must complete the following checklist to determine if the project is subject to Napa County's Construction Site Runoff Control Requirements. This form must be completed and submitted with your permit application(s). Definitions are provided in the Napa County Construction Site Runoff Control Requirements policy. **Note:** If multiple building or grading permits are required for a common plan of development, the total project shall be considered for the purpose of filling out this checklist.

# DETERMINING PROJECT APPLICABILITY TO THE CONSTRUCTION SITE RUNOFF CONTROL REQUIREMENTS

- ✓ If the answer to question 1 of Part A is "Yes" your project is subject to Napa County's Construction Site Runoff Control requirements and must prepare a Stormwater Pollution Prevention Plan (SWPPP). The applicant must also comply with the SWRCB's NPDES General Permit for Stormwater Associated with Construction Activity and must provide a copy of the Notice of Intent (NOI) and Waste Discharge Identification (WDID).
- ✓ If the answer to question 1 of Part A is "No", but the answer to any of the remaining questions is "Yes" your project is subject to Napa County's Construction Site Runoff Control requirements and must prepare a Stormwater Quality Management Plan (SQMP).
- ✓ If every question to Part A is answered "No" your project is exempt from Napa County's Construction Site Runoff Control Requirements, but must comply will all construction site runoff control standard conditions attached to any building or grading permit (see Appendix D of the Napa County Construction Site Runoff Control Requirements).
- ✓ If any of the answers to the questions in Part A is "Yes", complete the construction site prioritization in Part B below.

OVER

Page 1 of 2

Adopted Date: December 12, 2006

# NAPA COUNTY CONSTRUCTION SITE RUNOFF CONTROL REQUIREMENTS APPENDIX A – PROJECT APPLICABILITY CHECKLIST

		····	
Pai	t A: Determine Construction Phase Stormwater Requirements		
Wo	uld the project meet any of these criteria during construction?		
1.	Propose any soil disturbance of one acre or more?	***************************************	Yes No
2.	Does the project propose any soil disturbance greater than 10,000	square feet?	(Yes) No
3.	Does the project propose grading, earth moving, or soil disturbance greater?	e on slopes 15% or	Yes No
4.	Does the project propose earthmoving of 50 cubic yards or more?	•	Yes No
5.	Does the project propose soil disturbance within 50 feet of a stream and gutter, catch basin or storm drain that concentrates and transp to a "receiving water" (i.e., Waters of the State defined as all waters limited to, natural streams, creeks, rivers, reservoirs, lakes, ponds, lagoons, estuaries, bays, the Pacific Ocean, and ground water)?	orts stormwater runoffs, including but not	(Yes) No
Pai	t B: Determine Construction Site Priority		
pric and the	jects that are subject to the Construction Site Runoff Control Requirority of high, medium, or low. This prioritization must be completed we included in the SWPPP or SQMP. Indicate the project's priority in control below. The County reserves the right to adjust the priority of estruction.	ith this form, noted on to one of the checked box	the plans, es using
req	te: The construction priority does NOT change construction Best Ma uirements that apply to projects. The construction priority does affec be conducted by County staff and associated fees.	nagement Practice (BN t the frequency of insp	MP) ections that
⊠ ŀ	ect the highest priority category applicable to the project. High Priority (a) Projects with soil disturbance of one acre or greater.		
	b) Projects on slopes of 30% or greater.		
\	c) Projects proposing new storm drains.		
ו 🗆 א	Medium Priority a) Projects on slopes from 5% to 29%.		
•	b) Projects with soil disturbance between 10,000 sq. ft and one ac	ere.	
	c) Projects with earthmoving of 50 cubic yards or more.		
	<ul> <li>Priority</li> <li>Projects with soil disturbance within 50 feet stream, ditch, swale storm drain that concentrates and transports stormwater runoff</li> </ul>	e, curb and gutter, catc to a "receiving water".	h basin or
Nar	ne of Owner or Agent (Please Print):	Title:	
Sig	nature of Owner or Agent:	Date:	

Adopted Date: December 12, 2006 Page 2 of 2

# NAPA COUNTY POST-CONSTRUCTION RUNOFF MANAGEMENT REQUIREMENTS APPENDIX A – APPLICABILITY CHECKLIST

# Post-Construction Runoff Management Applicability Checklist

County of Napa Department of Public Works 1195 Third Street Napa, CA 94559 (707) 253-4351 for information



(Yes) No

Napa, CA 94559 (707) 253-4351 for information Project Address: Assessor Parcel Number(s): Project Number: (for County use Only) 221 Devlin Road, Napa, CA 94558 057-020-033 Instructions: Structural projects requiring a use permit, building permit, and/or grading permit must complete the following checklist to determine if the project is subject to the Post-Construction Runoff Management Requirements. In addition, the impervious surface worksheet on the reverse page must also be completed to calculate the amount of new and reconstructed impervious surfaces proposed by your project. This form must be completed, signed, and submitted with your permit application(s). Definitions are provided in the Post-Construction Runoff Management Requirements policy. Note: If multiple building or grading permits are required for a common plan of development. the total project shall be considered for the purpose of filling out this checklist. POST-CONSTRUCTION STORMWATER BMP REQUIREMENTS (Parts A and B) If any answer to Part A are answered "yes" your project is a "Priority Project" and is subject to the Site Design, Source Control, and Treatment Control design standards described in the Napa County Post-Construction Runoff Management Requirements. If all answers to Part A are "No" and any answers to Part B are "Yes" your project is a "Standard Project" and is subject to the Site Design and Source Control design standards described in the Napa County Post-Construction Runoff Management Requirements. If every question to Part A and B are answered "No", your project is exempt from post-construction runoff management requirements. Part A: Priority Project Categories Does the project meet the definition of one or more of the priority project categories? Residential with 10 or more units 2. Commercial development greater than 100,000 square feet..... 3. Automotive repair shop..... Retail Gasoline Outlet Restaurant..... Parking lots with greater than 25 spaces or greater than 5,000 square feet..... \*Refer to the definitions section for expanded definitions of the priority project categories. Part B: Standard Project Categories Does the project propose: 1. A facility that requires a NPDES Permit for Stormwater Discharges Associated with Industrial Activities?..... (Yes) No New or redeveloped impervious surfaces 10,000 square feet or greater, excluding roads?..... (Yes) No 3. Hillside residential greater than 30% slope..... Yes (No Roadway and driveway construction or reconstruction which requires a Grading Permit..... (Yes) No 5. Liquid or solid material loading and/or unloading areas?.... (Yes) No

Note: To find out if your project is required to obtain an individual General NPDES Permit for Stormwater discharges Associated with Industrial Activities, visit the State Water Resources Control Board website at, <a href="https://www.swrcb.ca.gov/stormwtr/industrial.html">www.swrcb.ca.gov/stormwtr/industrial.html</a>

Vehicle and/or equipment fueling, washing, or maintenance areas, excluding residential uses?
 Commercial or industrial waste handling or storage, excluding typical office or household waste?

Date: June 3, 2008 Page 1 of 2

# NAPA COUNTY POST-CONSTRUCTION RUNOFF MANAGEMENT REQUIREMENTS APPENDIX A – APPLICABILITY CHECKLIST

# **Impervious Surface Worksheet**

Project phasing to decrease impervious surface area shall not exempt the project from Post-Construction Runoff Management requirements. A new development or redevelopment project must comply with the requirements if it is part of a larger common plan of development that would result in the creation, addition and/or reconstruction of one acre or more of impervious surface. (For example, if 50% of a subdivision is constructed and results in 0.9 acre of impervious surface, and the remaining 50% of the subdivision is to be developed at a future date, the property owner must comply with the Post-Construction Runoff Management requirements.

		Total New and		
Type of Impervious Surface	Pre-Project (if applicable)	New (Does not replace any existing impervious area)	Reconstructed (Replaces existing impervious area)	Reconstructed Impervious Surfaces (Sq Ft)
Buildings, Garages, Carports, other Structures with roofs	0	15,369	0	15,369
Patio, Impervious Decking, Pavers and Impervious Liners	0	6,138	0	6,138
Sidewalks and paths	0	3,752	0	3,752
Parking Lots	0	2,967	0	2,967
Roadways and Driveways,	15,278	53,392	15,278	68,670
Off-site Impervious Improvements	0	0	0	0
Total Area of Impervious Surface (Excluding Roadways and Driveways)	0	28,226	0	28,226


Incorrect information on proposed activities or uses of a project may delay your project application(s) or permit(s).

I declare under penalty of perjury, that to the best of my knowledge, the information presented herein is accurate and complete.

	Name of Owner or Agent (Please Print):	Title:
ı		
ı		
l	Signature of Owner or Agent:	Date:
ı		
ı		
١		


Date: June 3, 2008 Page 2 of 2

ERMINAL JS AREA ALLIED CLEAN FUELS T EXISTING IMPERVIOU



3

# ALLIED CLEAN FUELS TERMINAL PROPOSED IMPERVIOUS AREAS



# NAPA COUNTY POST-CONSTRUCTION RUNOFF MANAGEMENT REQUIREMENTS APPENDIX B – APPLICATION FOR SRMP REVIEW

		FOR OFFI	CE USE ONLY		
SUBMITTAL DATE:		FILE #:	APN #:		_
USGS QUAD:		CalWat	ershed:		
REQUEST:					
USE PERMIT CATE	GORY: 🗆	Hillside Residence □ Subdiv	vision □ Commercial Facility	TYPE: ☐ Private ☐ !	Public
BUILDING AND/OR	GRADING	PERMIT: □ Structure □ □	)riveway □ Road □ Reservo	oir □ Cave □ Other	
FINAL APPROVAL:	Date:				
Deposit: \$					
Depo		Receipt Number	Received By		Date
		TO BE COMPLE	TED BY APPLICANT		
Applicant's Name: _	Stanley	(Please type Teaderman	e or print legibly)  Company: _Allied P	ropane Services	
Telephone #: ( <u>707</u>	) 252-5	500 <b>Fax #:</b> ( 707	<u> 255-8780</u> <b>E-Mail</b> :	stant@alliedproga	s.com
Mailing Address:	221	Devlin Road Street	Napa	CA	94558
			City	State	Zip
		t in Property: Owner	, , , , , , , , , , , , , , , , , , , ,		<del></del>
		Allied Propane Services			
	1	500 Fax #: ( 707) 255-		@alliedprogas.com	
Mailing Address:		Devlin Road Street	Napa City	<u>CA</u> State	94558 Zip
Site Address/Least		221 Devlin Road			Ζιρ
Site Address/Locati	***************************************	No Street		lapa City	
Assessor's Parcel #	:(s):	057-020-033			
			ined in this application, includ		
			(SRMP), the supplemental in		
			o the best of my knowledge. I rds as are deemed necessary		
Works for evaluation			reports related thereto, includi		
property involved.					
Signature of Applicar	nt	Date	Signature of Property Ow	ner Da	te .
orginatare of Applical		Date	orginature of Froperty Ow	no. Da	

Date: June 3, 2008 Page 1 of 1

# NAPA COUNTY CONSTRUCTION SITE RUNOFF CONTROL REQUIREMENTS APPENDIX C – SRMP CHECKLIST FOR A COMPLETE APPLICATION

FOR OFFICIAL USE ONLY

PLAN REVIEWER:	DATE RECEIVED:
PROJECT NAME:	PROJECT NUMBER:
PERMIT CATEGORY: ☐ Use Permit ☐ Build	ing Permit ☐ Grading Permit
Project Category (check all applicable P	riority or Standard Project categories)
⊠ Priority Project	□ Standard Project
Residential with 10 or more units	Industrial NPDES permit
100,000 sq ft commercial	Impervious surface > 10,000 sq ft (excluding roads)
Automotive repair shop	Hillside residential on slopes 30% or more
Restaurant	Roadways and driveways that require a grading permit
Retail Gasoline Outlet	New or alteration of storm drains
Parking Lot (>25 spaces or >5,000SF)	Liquid or solid material loading areas
	Vehicle or equipment fueling, washing, or maintenance
	Commercial or industrial waste handling and storage
At a minimum, the Stormwater Runoff Ma	nagement Plan must cover the areas listed below.
$\sqrt{\ }$ = Complete, X = Incomplete, NA = Not A	applicable
A. Planning and Organization  1. Completed Post-Construction B	MP Applicability Checklist (Appendix A)
2. Completed SRMP General Infor	mation Form (Appendix B).
2. Vicinity map showing the site in	relation to the surrounding area.
	rence other regulatory permits and their requirements. <b>Note:</b> All 0, 401/404, General Permit, etc) must be approved prior to any s.
4. Describe the nature of the propo	sed use of the de velopment project.
	of Concern proposing 10,000 or more sq. ft. of new impervious surface, ways or projects directly discharging to tidally-influenced

(e.g. storm drain, ditch, creek, etc) within 150 feet of the project footprint. Discretionary projects must also provide an analysis for all open stormwater conveyance systems. At a minimum, the analysis must consider the criteria in Chapter 3.3.

proposed project that have the potential to generate pollutants.

volume according to the criteria in Chapter 3.1.

receiving waters, must prepare a drainage study that calculates the pre-development runoff

Standard and Priority Projects must provide a completed Source Control BMP Selection Worksheet (Appendix E) that lists all anticipated activities associated with the use of the

Standard and Priority Projects must list and describe all stormwater conveyance systems

Date: June 3, 2008 Page 1 of 3

# NAPA COUNTY CONSTRUCTION SITE RUNOFF CONTROL REQUIREMENTS APPENDIX C – SRMP CHECKLIST FOR A COMPLETE APPLICATION

4. 👤

Priority Projects required to incorporate Treatment Control BMPs into the project design shall provide a completed Post-Construction BMP Selection Worksheet (Appendix F).

#### D. Post-Construction BMPs

### Site Design BMPs

- 1. List and describe all Site Design BMPs used to maintain stormwater runoff volumes to predevelopment conditions according to the criteria described in Chapter 4.1. If structural controls are required to maintain pre-development peak runoff conditions, a description of why Site Design BMPs alone are not practicable for maintaining runoff conditions is required.
- 2. List and describe all structures (outfalls, culverts, etc.) proposed within the jurisdiction of the DFG, RWQCB, and/or ACE. The description must include the structure's specifications and designed storm capacity. The structure must be constructed in accordance with all applicable State and Federal permits.
- 3. Provide the average slope and minimum and maximum distance between the project footpr int and all open stormwater conveyance systems (e.g. ditches, creeks, etc.). Ministerial projects must establish setbacks that comply with the stream setback requirements in the Conservation Regulations and Floodplain Management Regulations. Discretionary projects may establish and/or restore wider buffers zones to protect aquatic resources and structures.

#### Source Control BMPs

4. <u>√</u>

List and describe all source control measures included in the project design to eliminate pollutant contact with stormwater from the anticipated activities identified in the Source Control BMP Selection worksheet (Appendix E). The description must include the location and design specifications for each source control BMP.

#### Treatment Control BMPs

- 5. Priority Projects provide a completed Treatment Control BMP Selection Worksheet (Appendix F) and include a description of the location and design specifications for each treatment control BMP.
- 6. Provide the calculations used to design the treatment control BMPs to satisfy the numeric sizing treatment standards in Chapter 4.3. Applicants may count the site design BMPs toward meeting these numeric standards.

#### F. Site Plan


The site plan shall be neat and legible and shall be drawn on a 24"  $\times$  36" sheet and shall be folded to 8 ½" by 11" prior to submittal. When two or more sheets are used to illustrate the plan view, an index sheet is required, illustrating the entire project on one (1) 24"  $\times$  36" (minimum) sheet. The entire parcel shall be identified on the plan. If only a portion of the site will be developed, the entire parcel may be shown as a detail, with the area to be developed, cleared, and/or graded drawn to an appropriate scale.

The site plan shall include all of the following:

- 1. Provide and legend and north arrow on the plan.
- 2. Maximum plan scale of 1" = 100'.
- 3. An outline of the entire property.
- 4. Provide a "limit of disturbance" line which shows the limit of soil disturbance and areas where existing vegetation is preserved.

Date: June 3, 2008 Page 2 of 3

# NAPA COUNTY CONSTRUCTION SITE RUNOFF CONTROL REQUIREMENTS APPENDIX C – SRMP CHECKLIST FOR A COMPLETE APPLICATION



- 6. State and Federal wetlands must be accurately delineated.
- 7. The National Flood Insurance Program 100 Year Flood Zone and Flood Way must be delineated.
- 8. Drainage areas on the property and direction of flow. Map must extend as far outside the site perimeter as necessary to illustrate relevant drainage areas. Where relevant drainage areas are too large to depict on the map, map notes or inserts are sufficient.
- 9. All storm drain inlets and outlets must be located on the plan.
- 10. Anticipated stormwater discharge locations.
- 11. Location of existing and future Site Design and source Control BMPs.
- 12. Location of existing and future Treatment Control BMPs.
- 13. Location of existing and future "impervious" areas paved areas, buildings, covered areas.

# G. Post-Construction BMP Implementation and Maintenance Agreement

- 1. One of the maintenance mechanisms described in Chapter 5A, which is satisfactory to the Director, must be signed and executed.
- 2. Include a signed Owner's Certification that states "I, the undersigned, certify that all land clearing, construction and development shall be done pursuant to the approved plan." This must be signed in ink on each plan submitted or on an original reproducible.

Date: June 3, 2008 Page 3 of 3



# **ATTACHMENT 5**


**Treatment Control BMPs** 

Curb cut (or curb

to ensure runoff

capture)

inlet if needed



Not to Scale

4" min. dia. SDR 35 or equiv. min. 2" above overflow level sweep bend and cleanout

rim elevation around Walls as needed to establish constant access required; ahrum or beehive grafe preferred, Concrete drop inlet or 24' min x 36" min. if manhole with frame. Overflow structure

1/4 " openings

Min. 6 3' max. mulch if specified in

perimeter of facility

Schedule 80 (no perforations) seal penetration with grout landscape plans

Install all plantings to maintain

splash biock Cobbles or

Top of Soil Layer TSL

pavement Adjacent

TSL at or below specified

elevation

Specified soil mix

Min. 18\*

Top of Gravel Layer TGL 🥀

Bend or slope so discharge is at – TGL elevation

4 ' min. dia. SDR 35 or equiv.,

perforations facing down

permeable

material

Bottom of Gravel Layer BGL 🖖

Class 2

Min. 12"

, ← 24"

approved discharge

point

To storm drain or

Native soil, no compaction. Rip to lossen.

# Allowed variations for special site conditions:

needed to protect pavement or structures

Cutoff wall if


- Facilities located within 10 feet of structures or other potential geotechnical hazards may incorporate an impervious cutoff wall
- Facilities with documented high concentrations of pollutants in underlying soil or groundwater, facilities where infiltration could contribute to a geotechnical hozard, and facilities located on elevated plazas or other structures may incorporate an impervious liner and may locate the underdrain discharge at the BGL (flow-through planter configuration).
- underdrain to a surface drain or subsurface storm drain are infeasible may omit fire underdrain. Facilities located in areas of high groundwater, highly infiltrative soils, or where connection the

- No liner, no filter fabric, no landscape cloth.
   Maintain BGL. TGL, TSL throughout facility area at elevations to be specified in plan.
  - Class 2 perm layer may extend below and underneath drop inlet.
    - Elevation of underdrain discharge is at top of gravel layer. See Chapter 4 for instructions on facility sizing and additional
      - specifications.

44 60

# **Bioretention Facility**

Plan (Not to Scale)



Note: Call out elevations of curb, pavement, inlet, top of soil layer (TSL), bottom of soil layer (BSL), and bottom of gravel layer (BGL) at all inlets and outlets and at key points along edge of facility.



# **ATTACHMENT 6**

# **OWNER'S CERTIFICATION**

# **OWNER'S CERTIFICATION**

	Company/Corporation/Partnership Name		
	Ву:	*****	
	(Type Name)		
	(Type Title)		
E OF			